

Fișa cu date de securitate

ADYWOOD 2K COMP.A

Fișa cu date de securitate din data 10/09/2024 versiunea 2

SECȚIUNEA 1: Identificarea substanței/amestecului și a societății/întreprinderii

1.1. Identificator de produs

Identificarea preparatului:

Nume comercial: ADYWOOD 2K COMP.A

Cod comercial: 580

UFI: 7TK1-G0VK-V008-AK3U

1.2. Utilizări relevante identificate ale substanței sau ale amestecului și utilizări contraindicate

Utilizarea recomandată: Adeziv bicomponent pentru pardoseli din lemn

1.3. Detalii privind furnizorul fișei cu date de securitate

Compania: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Responsabil: laboratorio.spresiano@fassabortolo.it

1.4. Număr de telefon care poate fi apelat în caz de urgență

+40213183606

SECȚIUNEA 2: Identificarea pericolelor



2.1. Clasificarea substanței sau a amestecului

Regulamentul (CE) nr. 1272/2008 (CLP)

Skin Irrit. 2 Provoacă iritarea pielii.
Eye Irrit. 2 Provoacă o iritare gravă a ochilor.
Skin Sens. 1 Poate provoca o reacție alergică a pielii.
Aquatic Chronic 3 Nociv pentru mediul acvatic cu efecte pe termen lung.
Efecte fizico-chimice dăunătoare sănătății omului și mediului înconjurător:
Nici un alt risc

2.2. Elemente de etichetare

Regulamentul (CE) nr. 1272/2008 (CLP)

Pictograme de pericol și cuvânt de avertizare



Atenție

Fraze de pericol

H315 Provoacă iritarea pielii.
H317 Poate provoca o reacție alergică a pielii.
H319 Provoacă o iritare gravă a ochilor.
H412 Nociv pentru mediul acvatic cu efecte pe termen lung.

Fraze de precauție

P261 Evitați să inspirați vaporii.
P264 Spălați-vă bine cu săpun și apă din abundență după utilizare.
P280 Purtați mănuși de protecție și protejați ochii/vederea.
P333+P313 În caz de iritare a pielii sau de erupție cutanată: consultați medicul.
P362+P364 Scoateți îmbrăcămintea contaminată și spălați-o înainte de reutilizare.

Prevederi speciale:

EUH205 Conține componenți epoxidici. Poate provoca o reacție alergică.

Conține:

oxiran, derivați mono[(alchiloxi C12-14)metil].

Ulei de nucă de caju

bis-[4-(2,3-epoxipropoxi)fenil]propan

Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului

Dispoziții speciale conform Anexei XVII (REACH) cu modificările și completările ulterioare:

Nici una

2.3. Alte pericole

PBT, vPvB sau perturbatori endocrini prezenți în concentrații >= 0,1%:

Componentă	Nr. de Ident.	Cantitate	Proprietăți:
Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului	EINECS: 700-960-7	>=1 - <3 %	vPvB

Nici un alt risc

SECȚIUNEA 3: Compoziție/informații privind componenții

3.1. Substanțe

N.A.

3.2. Amestecuri

Identificarea preparatului: ADYWOOD 2K COMP.A

Componente periculoase în sensul Regulamentului CLP și clasificarea corespunzătoare:

Cantitate	Nume	Nr. de Ident.	Clasificare	Număr de înregistrare:	Proprietăți:
≥5 - <10 %	bis-[4-(2,3-epoxipropoxi)fenil]propan	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Limite de concentrație specifice: 5% ≤ C < 100%: Skin Irrit. 2 H315 5% ≤ C < 100%: Eye Irrit. 2 H319	01-2119456619-26-xxxx	
≥1 - <3 %	acetat de etil	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	01-2119475103-46-xxxx	
≥1 - <3 %	Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului	EC:700-960-7	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	01-2119555274-38-xxxx	vPvB
≥1 - <3 %	oxiran, derivați mono[(alchiloxi C12-14)metil].	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315 Skin Sens. 1, H317	01-2119485289-22-xxxx	
≥1 - <3 %	Ulei de nucă de caju	CAS:8007-24-7 EC:700-991-6	Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Irrit. 2, H315 Skin Sens. 1A, H317 Toxicitate Acută Estimată: ATE - Oral: 500mg/kg gc ATE - Dermică: 1100mg/kg gc	01-2119502450-57-xxxx	

SECȚIUNEA 4: Măsurile de prim ajutor

4.1. Descrierea măsurilor de prim ajutor

În caz de contact cu pielea:

Îndepărtați imediat hainele contaminate și eliminați-l în mod sigur.

Zonele corpului care au venit, sau se presupune numai că au venit, în contact cu produsul trebuie spălate imediat și abundent cu apă curentă.

Spălați complet corpul (duș sau baie).

În caz de contact cu ochii:

În caz de contact cu ochii, clătiți cu apă pentru un interval de timp corespunzător și țineți deschise pleoapele, după care consultați imediat un oftalmolog.

Protejați ochiul lezat.

În caz de ingerare:

Nu provocați vomitarea, adresați-vă unui medic arătând Fișa de Siguranță și eticheta produsului.

În caz de inhalare:

Conduceți accidentatul la aer liber și țineți-l la cald și în repaus.

4.2. Cele mai importante simptome și efecte, atât acute, cât și întârziate

Simptomele și efectele sunt cele preconizate în secțiunea 2 cu privire la pericole.

4.3. Indicații privind orice fel de asistență medicală imediată și tratamentele speciale necesare

În caz de accident sau stare proastă consultați imediat un medic (dacă este posibil arătați instrucțiunile de folosință sau fișa de siguranță).

SECȚIUNEA 5: Măsurile de combatere a incendiilor

5.1. Mijloace de stingere a incendiilor

Mijloace de stingere corespunzătoare:

CO₂, stingătoare cu pulbere, spumă, apă pulverizată.

Mijloace de stingere care nu trebuie să fie utilizate din motive de siguranță:

Jeturi de apă.

5.2. Pericole speciale cauzate de substanță sau de amestec

Combustia produce fum greu.

Nu inhalați gazele produse prin explozie și/sau prin combustie (monoxid de carbon, dioxid de carbon, oxizi de azot).

5.3. Recomandări destinate pompierilor

Folosiți dispozitive respiratorii corespunzătoare.

Strângeți separat apa contaminată folosită pentru stingerea incendiului. Nu o descărcați în rețeaua de canalizare.

Dacă este posibil din punct de vedere al siguranței, îndepărtați din zona de pericol imediat recipientele neafectate.

SECȚIUNEA 6: Măsurile împotriva pierderilor accidentale

6.1. Precauții personale, echipament de protecție și proceduri de urgență

Pentru personalul care nu este implicat în situații de urgență:

Îmbrăcați dispozitivele de protecție individuală.

Duceți persoanele în loc sigur.

Citiți măsurile de protecție prezentate la punctele 7 și 8.

Pentru personalul care intervine în situații de urgență:

Îmbrăcați dispozitivele de protecție individuală.

6.2. Precauții pentru mediul înconjurător

Împiedicați penetrarea în sol/subsol. Împiedicați vărsarea în apele de suprafață sau în rețeaua de canalizare.

În caz de scurgere de gaz sau penetrare în cursuri de apă, sol sau sistemul de canalizare, informați autoritățile răspunzătoare.

6.3. Metode și material pentru izolarea incendiilor și pentru curățenie

Material corespunzător pentru colectare: material absorbant inert (de exemplu, nisip, vermiculit)

Dupa ce produsul a fost recuperat, clătiți suprafața și materialele folosite cu apă

Rețineți apa de spălat contaminată și eliminați-o.

6.4. Trimiteri către alte secțiuni

Vezi și paragrafele 8 și 13

SECȚIUNEA 7: Manipulare și depozitare

7.1. Precauții pentru manipularea în condiții de securitate

Evitați contactul cu pielea și ochii, precum și inhalarea vaporilor și a ceții.

Nu folosiți recipiente goale înainte de a fi curățate.

Înainte de operațiunile de transfer, asigurați-vă că în recipiente nu sunt materiale reziduale incompatibile.

Sfaturi privind igiena generală la locul de muncă:

Hainele contaminate trebuie înlocuite înainte de accesul la zona de prânz.

Nu mincați sau beți în timpul lucrului

Se face trimitere și la paragraful 8 pentru dispozitivele de protecție recomandate.

7.2. Condiții de depozitare în condiții de securitate, inclusiv eventuale incompatibilități

Păstrați recipientele bine închise într-un spațiu răcoros și bine ventilat, la distanță de surse de căldură.

Țineți departe de alimente, băuturi și hrană pentru animale.

Materiale incompatibile

Vezi pct. 10.5

Instructiuni privind spatiile de depozitare:
Spatii ventilate adecvat

7.3. Utilizare (utilizări) finală (finale) specifică (specifice)

Recomandări

Vezi pct. 1.2

Soluții specifice pentru sectorul industrial

Nici o utilizare particulară

SECȚIUNEA 8: Controale ale expunerii/protecția personală

8.1. Parametri de control

Lista componentelor cu valoarea OEL

acetat de etil

CAS: 141-78-6	Tip OEL	ACGIH	Termen lung 400 ppm Note: URT and eye irr
	Tip OEL	UE	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	MAK Austria	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	MAK Germania	Termen lung 750 mg/m3 - 200 ppm; Termen scurt 1500 mg/m3 - 400 ppm
	Tip OEL	VLEP Belgia	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	VLEP Franța	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	VLEP Italia	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	VLEP România	Termen lung 400 mg/m3 - 111 ppm; Termen scurt 500 mg/m3 - 139 ppm
	Tip OEL	TLV Bulgaria	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	TLV Cehia	Termen lung 700 mg/m3 - 191.1 ppm; Termen scurt 900 mg/m3 - 245.7 ppm
	Tip OEL	VLA Spania	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1460 mg/m3 - 400 ppm
	Tip OEL	ÁK Ungaria	Termen lung 1400 mg/m3; Termen scurt 1400 mg/m3
	Tip OEL	VLE Portugalia	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	SUVA Elveția	Termen lung 730 mg/m3 - 200 ppm; Termen scurt 1470 mg/m3 - 400 ppm
	Tip OEL	WEL U.K.	Termen lung 730 mg/m3 - 200 ppm; Termen scurt 1460 mg/m3 - 400 ppm
	Tip OEL	GVI Croația	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	AGW Germania	Termen lung 730 mg/m3 - 200 ppm; Termen scurt 1460 mg/m3 - 400 ppm
	Tip OEL	NDS Polonia	Termen lung 734 mg/m3; Termen scurt 1468 mg/m3
	Tip OEL	MV Slovenia	Termen lung 734 mg/m3 - 200 ppm; Termen scurt 1468 mg/m3 - 400 ppm
	Tip OEL	IPRV Lituania	Termen lung 500 mg/m3 - 150 ppm; Termen scurt 1100 mg/m3 - 300 ppm

Valori limită de expunere PNEC

bis-[4-(2,3-epoxipropoxi)fenil]propan

CAS: 1675-54-3	Cale de expunere: Apă dulce; PNEC Limită: 0.006 mg/l
	Cale de expunere: Apă sărată; PNEC Limită: 0.001 mg/l
	Cale de expunere: Sedimente în apă dulce; PNEC Limită: 0.341 mg/kg
	Cale de expunere: Sedimente în apă sărată; PNEC Limită: 0.034 mg/kg
	Cale de expunere: Sol (agricol); PNEC Limită: 0.065 mg/kg
	Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 10 mg/l

acetat de etil

CAS: 141-78-6	Cale de expunere: Apă sărată; PNEC Limită: 0.024 mg/l
	Cale de expunere: Apă dulce; PNEC Limită: 0.24 mg/l
	Cale de expunere: Sedimente în apă sărată; PNEC Limită: 0.115 mg/kg
	Cale de expunere: Sedimente în apă dulce; PNEC Limită: 1.15 mg/kg
	Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 650 mg/l
	Cale de expunere: Sol (agricol); PNEC Limită: 0.148 mg/kg

Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului

Cale de expunere: Apă dulce; PNEC Limită: 0.014 mg/l
Cale de expunere: Apă sărată; PNEC Limită: 0.001 µg/l
Cale de expunere: Sedimente în apă dulce; PNEC Limită: 1064 mg/kg
Cale de expunere: Sedimente în apă sărată; PNEC Limită: 106 mg/kg

Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 2.4 mg/l

Cale de expunere: Sol (agricol); PNEC Limită: 212.2 mg/kg

oxiran, derivați mono[(alchiloxi C12-14)metil].

CAS: 68609-97-2 Cale de expunere: Apă dulce; PNEC Limită: 0.106 mg/l

Cale de expunere: Apă sărată; PNEC Limită: 0.011 mg/l

Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 10 mg/l

Cale de expunere: Sedimente în apă sărată; PNEC Limită: 30.72 mg/kg

Cale de expunere: Sedimente în apă dulce; PNEC Limită: 307.16 mg/kg

Cale de expunere: Sol; PNEC Limită: 1.234 mg/kg

Ulei de nucă de caju

CAS: 8007-24-7 Cale de expunere: Apă dulce; PNEC Limită: 0.003 mg/l

Cale de expunere: Apă sărată; PNEC Limită: 0.03 mg/l

Cale de expunere: Sedimente în apă dulce; PNEC Limită: 0.97 mg/kg

Cale de expunere: Sedimente în apă sărată; PNEC Limită: 0.088 mg/kg

Cale de expunere: Sol (agricol); PNEC Limită: 6.71 mg/kg

Nivel Derivat Fără Efect (DNEL)

bis-[4-(2,3-epoxipropoxi)fenil]propan

CAS: 1675-54-3 Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 0.75 mg/kg; Consumator: 0.089 mg/kg

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 4.93 mg/m³; Consumator: 0.87 mg/m³

Cale de expunere: Oral uman; Frecvență de expunere: Pe termen scurt, efecte sistemice
Consumator: 0.5 mg/kg

acetat de etil

CAS: 141-78-6 Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 734 mg/m³; Consumator: 367 mg/m³

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte locale
Lucrător profesionist: 734 mg/m³; Consumator: 367 mg/m³

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen scurt, efecte sistemice
Lucrător profesionist: 1468 mg/m³; Consumator: 734 mg/m³

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen scurt, efecte locale
Lucrător profesionist: 1468 mg/m³; Consumator: 734 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 63 mg/kg; Consumator: 37 mg/kg

Cale de expunere: Oral uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Consumator: 4.5 mg/kg

Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului

Cale de expunere: Oral uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Consumator: 0.2 mg/kg

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 1.4 mg/m³; Consumator: 0.35 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Consumator: 1.7 mg/kg

oxiran, derivați mono[(alchiloxi C12-14)metil].

CAS: 68609-97-2 Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 3.6 mg/m³; Consumator: 0.87 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 1 mg/kg; Consumator: 0.5 mg/kg

Cale de expunere: Oral uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Consumator: 0.5 mg/kg

Ulei de nucă de caju

CAS: 8007-24-7 Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice

Lucrător profesionist: 0.88 mg/m³; Consumator: 0.2 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 0.5 mg/kg; Consumator: 0.25 mg/kg

Cale de expunere: Oral uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Consumator: 0.25 mg/kg

8.2. Controale ale expunerii

Asigurați o ventilație adecvată. Atunci când este rezonabil posibil, aceasta se poate obține prin utilizarea de ventilație de schimb și a unei aspirații generale bune.

Protecția ochilor

Ochelari cu protecție laterală (EN 166).

Protecția pielii

Utilizați îmbrăcăminte corespunzătoare pentru protecția completă a pielii, în funcție de activitate și expunere (EN 14605/EN 13982), de exemplu salopetă de lucru, șorț, încălțăminte de siguranță, îmbrăcăminte corespunzătoare.

Protecția mainilor

Nu există niciun material sau combinație de materiale pentru mănuși care să poată garanta o rezistență nelimitată la orice produs chimic sau combinație de produse.

Pentru manipulare prelungită sau repetată, utilizați mănuși rezistente la produse chimice.

Tipul de mănuși adecvate (EN 374/EN 16523); FKM (fluor cauciuc): grosime ≥ 0.4 mm; timp de penetrare ≥ 480 min. NBR (cauciuc nitrilic): grosime ≥ 0.4 mm; timp de penetrare ≥ 480 min

Alegerea mănușilor potrivite nu depinde numai de material, ci și de alte caracteristici de calitate care variază de la un producător la altul, precum și de metodele și timpii de utilizare a amestecului.

Protecție respiratorie

Dacă lucrătorii sunt expuși la concentrații mai mari decât limitele de expunere, trebuie să poarte aparate respiratorii certificate.

Filtru amestec (EN 14387): mască cu filtru A-P2.

Controale de expunere ambientală:

Vezi pct. 6.2

Măsurile de igienă și tehnice

Vezi alineatul 7.

SECȚIUNEA 9: Proprietățile fizice și chimice

9.1. Informații privind proprietățile fizice și chimice de bază

Aspect: lichid păstos

Culoare: maro închis

Miros: caracteristic

Punctul de topire/punctul de înghețare: N.D.

Punctul de fierbere sau punctul inițial de fierbere și intervalul de fierbere: N.D.

Inflamabilitatea: N.A.

Limita inferioară și superioară de explozie: N.D.

Punctul de aprindere: $> 60^{\circ}\text{C}$ / 93°C

Temperatura de autoaprindere: N.D.

Temperatura de descompunere: N.D.

pH: N.A. (Nu se aplică datorită naturii produsului)

Viscozitatea cinematică: $> 20.5 \text{ mm}^2/\text{s}$ (40°C)

Densitatea și/sau densitatea relativă: $1,8 \text{ kg/l}$ (Metoda internă)

Densitatea relativă a vaporilor: N.D.

Presiunea vaporilor: N.D.

Solubilitatea în apă: Imiscibil

Solubilitate în ulei: N.A.

Coeficientul de partiție n-octanol/apă (valoarea log): N.A.

Caracteristicile particulei:

Dimensiunea particulei: N.A.

9.2. Alte informații

Conductivitatea: N.D.

Proprietati explozive: N.A. (Evaluare internă)

Proprietati oxidante: N.A. (Evaluare internă)

Viteza de evaporare: N.A.

SECȚIUNEA 10: Stabilitate și reactivitate

10.1. Reactivitate

Stabilă în condiții normale

10.2. Stabilitate chimică

Stabilă în condiții normale

10.3. Posibilitatea de reacții periculoase

Se poate aprinde în contact cu agenți puternic oxidanți

Din cauza efectului căldurii sau în caz de incendiu, se pot elibera oxizi de carbon și vapori care pot fi dăunători pentru sănătate.

10.4. Condiții de evitat

Evitați apropierea de surse de căldură.

10.5. Materiale incompatibile

Agenți de oxidare puternici, agenți de reducere puternici, amine alifatice și aromatice.

Vezi pct. 10.3

10.6. Prođuși de descompunere periculoși

În cazul depozitării și manipulării adecvate, nu există produse de descompunere periculoase.

Vezi pct. 5.2

SECȚIUNEA 11: Informații toxicologice

11.1. Informații privind clasele de pericol definite în Regulamentul (CE) nr. 1272/2008

Rasina epoxi lichida continuta de acest material produse doar iritari minore ale pielii. Oricum, toate rasinile epoxi sunt capabile sa produca sensibilizarea pielii. Susceptibilitatea la sensibilizare si iritare a pielii difera de la persoana la persoana

La indivizii sensibilizati dermatita alergica poatesa nu apara decat la cateva zile sau saptamani dupa contactul frecvent sau prelungit. De aceea, chiar daca potentialul de iritare al pielii este scazut, contactul cu pielea trebuie evitat

Odata sensibilitatea instalata, expunerea pielii la cantitati foarte mici de material poate cauza eritem sau edem

Informații toxicologice ale produsului:

a) toxicitate acută	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
b) corodarea/iritarea pielii	Produsul este clasificat: Skin Irrit. 2(H315)
c) lezarea gravă/iritarea ochilor	Produsul este clasificat: Eye Irrit. 2(H319)
d) sensibilizarea căilor respiratorii sau a pielii	Produsul este clasificat: Skin Sens. 1(H317)
e) mutagenitatea celulelor germinative	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
f) cancerogenitatea	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
g) toxicitatea pentru reproducere	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
h) STOT (toxicitate asupra organelor țintă specifice) - expunere unică	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
i) STOT (toxicitate asupra organelor țintă specifice) - expunere repetată	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
j) pericol prin aspirare	Neclasificat
	Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.

Informații toxicologice referitoare la substanțele principale găsite în acest produs:

bis-[4-(2,3-epoxipropoxi)fenil]propan

CAS: 1675-54-3 a) toxicitate acută LD50 Oral Șobolan > 2000 mg/kg
LD50 Piele Șobolan > 2000 mg/kg

acetat de etil

CAS: 141-78-6 a) toxicitate acută LD50 Oral Șobolan 4934 mg/kg
LD50 Piele Iepure > 20000 mg/kg
LC50 Vapori de inhalare Șobolan > 22.5 mg/l 6h

Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului

a) toxicitate acută LD50 Piele Șobolan > 2000 mg/kg
LD50 Oral Șobolan > 2000 mg/kg

oxiran, derivați mono[(alchiloxi C12-14)metil].

CAS: 68609-97-2 a) toxicitate acută LC0 Vapori de inhalare Șobolan > 0.15 mg/l 7h
LD50 Oral Șobolan > 2000 mg/kg
LD50 Piele Iepure > 4000 mg/kg

Ulei de nucă de caju

CAS: 8007-24-7 a) toxicitate acută ATE - Oral: 500 mg/kg gc
ATE - Dermică: 1100 mg/kg gc
LD50 Piele Șobolan > 2000 mg/kg
LD50 Oral Șobolan 5000 mg/kg

11.2. Informații privind alte pericole

Proprietăți de perturbator endocrin:

Nu conține perturbatori endocrini prezenți în concentrații $\geq 0,1\%$

SECȚIUNEA 12: Informații ecologice

A se adopta bune practici de producție astfel încât produsul să nu fie eliberat în mediu

12.1. Toxicitate

Informații Ecotoxicologice:

Nociv pentru mediul acvatic cu efecte pe termen lung.

Lista proprietăților Eco-toxicologice ale produsului

Produsul este clasificat: Aquatic Chronic 3(H412)

Lista componentelor cu proprietăți ecotoxicologice

bis-[4-(2,3-epoxipropoxi)fenil]propan

CAS: 1675-54-3 a) Toxicitate acvatică acută: EC50 Daphnia 1.8 mg/l 48h
a) Toxicitate acvatică acută: LC50 Pește 2 mg/l 96h
a) Toxicitate acvatică acută: EC50 Alge 11 mg/l 72h
b) Toxicitatea acvatică cronică: NOEC Daphnia 0.3 mg/l 21d

acetat de etil

CAS: 141-78-6 a) Toxicitate acvatică acută: LC50 Pește 230 mg/l 96h
a) Toxicitate acvatică acută: EC50 Daphnia 165 mg/l 48h

oxiran, derivați mono[(alchiloxi C12-14)metil].

CAS: 68609-97-2 a) Toxicitate acvatică acută: LL50 Pește > 100 mg/l 96h
a) Toxicitate acvatică acută: EL50 Daphnia 7.2 mg/l 48h
a) Toxicitate acvatică acută: IC50 Alge 843.75 mg/l 72h

12.2. Persistență și degradabilitate

bis-[4-(2,3-epoxipropoxi)fenil]propan

CAS: 1675-54-3 Degradabil în mod lent

acetat de etil

CAS: 141-78-6 Degradabil în mod rapid

oxiran, derivați mono[(alchiloxi C12-14)metil].

CAS: 68609-97-2 Degradabil în mod rapid

Ulei de nucă de caju

CAS: 8007-24-7 Degradabil în mod rapid

12.3. Potențial de bioacumulare

N.A.

12.4. Mobilitate în sol

N.A.

12.5. Rezultatele evaluărilor PBT și vPvB

Lista componentelor cu proprietăți ecotoxicologice

Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului

$\geq 1 - < 3\%$ vPvB

12.6. Proprietăți de perturbator endocrin

Nu conține perturbatori endocrini prezenți în concentrații $\geq 0,1\%$

12.7. Alte efecte adverse

N.A.

SECȚIUNEA 13: Considerații privind eliminarea

13.1. Metode de tratare a deșeurilor

A se recupera, dacă este posibil. A se respecta regulamentele locale în vigoare

Nu permiteți pătrunderea produsului în sistemul de canalizare sau în cursurile de apă.

Recipientele contaminate cu produs, în conformitate cu dispozițiile legale locale sau naționale.

Odată ce produsul a expirat, acesta trebuie eliminat în conformitate cu reglementările în vigoare.

SECȚIUNEA 14: Informații referitoare la transport

Nu sunt clasificate ca periculoase din punct de vedere al regulamentelor de transport

14.1. Numărul ONU sau numărul de identificare

N/A

14.2. Denumirea corectă ONU pentru expediție

ADR-Nume transport îmbarcare: N/A

IATA-Nume transport îmbarcare: N/A

IMDG-Nume transport îmbarcare: N/A

14.3. Clasa (clasele) de pericol pentru transport

ADR-clasa: N/A

IATA-Clasa: N/A

IMDG-Clasa: N/A

14.4. Grupul de ambalare

ADR-Grup Ambalare: N/A

IATA-Grup Ambalare: N/A

IMDG-Grup Ambalare: N/A

14.5. Pericole pentru mediul înconjurător

Poluant marin: Nu

Poluant ambiental: Nu

IMDG-EMS: N/A

14.6. Precauții speciale pentru utilizatori

Drumuri și Căi Ferate (ADR-RID):

scutiri ADR:

ADR-Etichetă: N/A

ADR - Număr de identificare a pericolului: N/A

ADR-Dispoziții Speciale: N/A

ADR-Cod de restricție în tunel:

Aer (IATA):

IATA-Aeronavă de pasagerit: N/A

IATA-Aeronavă de marfă: N/A

IATA-Etichetă: N/A

IATA-Riscul secundar: N/A

IATA-Erg: N/A

IATA-Dispoziții Speciale: N/A

Mare (IMDG):

IMDG-Depozitare și manipulare: N/A

IMDG-Segregare: N/A

IMDG-Riscul secundar: N/A

IMDG-Dispoziții Speciale: N/A

14.7. Transportul maritim în vrac în conformitate cu instrumentele OMI

N.A.

SECȚIUNEA 15: Informații de reglementare

15.1. Regulamente/legislație în domeniul securității, al sănătății și al mediului specifice (specifică) pentru substanța sau amestecul în cauză

Directiva 98/24/CE (Riscuri în legătură cu agenții chimici la locul de muncă)

Directiva 2000/39/CE (Valori limită a expunerii profesionale)

Directiva 2010/75/UE

Regulamentul (CE) nr. 1907/2006 (REACH)

Regulamentul (CE) nr. 1272/2008 (CLP)

Regulamentul (CE) nr. 790/2009 (ATP 1 CLP) și (EU) nr. 758/2013

- Regulamentul (EU) nr. 2020/878
- Regulamentul (EU) nr. 286/2011 (ATP 2 CLP)
- Regulamentul (EU) nr. 618/2012 (ATP 3 CLP)
- Regulamentul (EU) nr. 487/2013 (ATP 4 CLP)
- Regulamentul (EU) nr. 944/2013 (ATP 5 CLP)
- Regulamentul (EU) nr. 605/2014 (ATP 6 CLP)
- Regulamentul (EU) nr. 2015/1221 (ATP 7 CLP)
- Regulamentul (EU) nr. 2016/918 (ATP 8 CLP)
- Regulamentul (EU) nr. 2016/1179 (ATP 9 CLP)
- Regulamentul (EU) nr. 2017/776 (ATP 10 CLP)
- Regulamentul (EU) nr. 2018/669 (ATP 11 CLP)
- Regulamentul (EU) nr. 2018/1480 (ATP 13 CLP)
- Regulamentul (EU) nr. 2019/521 (ATP 12 CLP)
- Regulamentul (EU) nr. 2020/217 (ATP 14 CLP)
- Regulamentul (EU) nr. 2020/1182 (ATP 15 CLP)
- Regulamentul (EU) nr. 2021/643 (ATP 16 CLP)
- Regulamentul (EU) nr. 2021/849 (ATP 17 CLP)
- Regulamentul (EU) nr. 2022/692 (ATP 18 CLP)

Restricții referitoare la produsele sau substanțele conținute de acestea conform Anexei XVII Regulamentul (CE) 1907/2006 (REACH) cu modificările ulterioare:

Restricții referitoare la produs: 3
Restricții referitoare la substanțele conținute: 40, 75

Dispoziții în legătură cu directiva EU 2012/18 (Seveso III):

Nici una

Regulamentul (UE) nr. 649/2012 (Regulamentul PIC)

Nu există substanțe menționate

Clasa Germană a Periculozității Apei

Clasa 2: periculos pentru ape.

Substanțe SVHC:

Substanțe din lista candidatelor (Art. 59 Reg. 1907/2006, REACH):

Componentă	Nr. de Ident.	Cantitate	Proprietăți:
Produse de reacție de oligomerizare și alchilare a 2-fenilpropenă și fenolului	EINECS: 700-960-7	>=1 - <3 %	SVHC - vPvB

15.2. Evaluarea securității chimice

Nu a fost efectuată nici o Evaluare de Securitate Chimică pentru amestecul

SECȚIUNEA 16: Alte informații

Cod	Descriere
EUH066	Expunerea repetată poate provoca uscarea sau crăparea pielii.
H225	Lichid și vapori foarte inflamabili.
H302	Nociv în caz de înghițire.
H312	Nociv în contact cu pielea.
H315	Provoacă iritarea pielii.
H317	Poate provoca o reacție alergică a pielii.
H318	Provoacă leziuni oculare grave.
H319	Provoacă o iritare gravă a ochilor.
H336	Poate provoca somnolență sau amețeală.
H411	Toxic pentru mediul acvatic cu efecte pe termen lung.
H412	Nociv pentru mediul acvatic cu efecte pe termen lung.

Cod	Clasa de pericol și categoria de pericol	Descriere
2.6/2	Flam. Liq. 2	Lichid inflamabil, Categoria 2
3.1/4/Dermal	Acute Tox. 4	Toxicitate acută (dermică), Categoria 4
3.1/4/Oral	Acute Tox. 4	Toxicitate acută (orală), Categoria 4
3.2/2	Skin Irrit. 2	Iritarea pielii, Categoria 2
3.3/1	Eye Dam. 1	Lezarea gravă a ochilor, Categoria 1

3.3/2	Eye Irrit. 2	Iritarea ochilor, Categoria 2
3.4.2/1	Skin Sens. 1	Sensibilizarea pielii, Categoria 1
3.4.2/1A	Skin Sens. 1A	Sensibilizarea pielii, Categoria 1A
3.4.2/1B	Skin Sens. 1B	Sensibilizarea pielii, Categoria 1B
3.8/3	STOT SE 3	Toxicitate asupra unui organ țintă specific – o singură expunere, Categoria 3
4.1/C2	Aquatic Chronic 2	Pericol cronic (pe termen lung) pentru mediul acvatic, Categoria 2
4.1/C3	Aquatic Chronic 3	Pericol cronic (pe termen lung) pentru mediul acvatic, Categoria 3

Clasificarea și procedura utilizate pentru realizarea clasificării pentru amestecuri în conformitate cu Regulamentul (CE) nr. 1272/2008 [CLP]:

Clasificare conform Regulamentului (CE) nr. 1272/2008	Procedura de clasificare
Skin Irrit. 2, H315	Metoda de calcul
Eye Irrit. 2, H319	Metoda de calcul
Skin Sens. 1, H317	Metoda de calcul
Aquatic Chronic 3, H412	Metoda de calcul

Acest document a fost întocmit de un tehnician competent în domeniul SDS și care este pregătit în mod corespunzător.

Principalele surse bibliografice:

ECDIN - Rețeaua de date și informații de mediu privind produsele chimice - Centrul comun de cercetare, Comisia Comunităților Europene

SAX PROPRIETĂȚI PERICULOASE ALE MATERIALELOR INDUSTRIALE - Ediția a opta - Van Nostrand Reinold

Fișe tehnice de securitate ale furnizorilor de materii prime.

Aceste informații se bazează pe cunoștințele deținute la data menționată mai sus. Se referă numai la produsul menționat și nu constituie o garanție a calității pentru cazurile particulare

Este de datoria utilizatorului să se asigure că aceste informații sunt adecvate și corespund domeniului specific de utilizare

Această FTS anulează și înlocuiește pe cele emise anterior.

Legenda cu abrevierile și acronimele folosite în fișa cu date de securitate

ACGIH: Conferința Americană a Igieniştilor Industriali Guvernamentali

ADR: Acordul European referitor la Încărcătura Internațională de Bunuri Periculoase pe Drumuri

ATE: Toxicitate Acută Estimată

ATEmix: Estimarea toxicității acute (Amestecuri)

BEI: Index de Expunere Biologică

CAS: Chemical Abstracts Service (departament al Societății Americane de Chimie)

CAV: Centrul de Otrăvuri

CE: Comunitatea Europeană

CLP: Clasificare, Etichetare, Ambalare

CMR: Cancerigene, Mutagene și Toxice pentru reproducere

COV: Compus Organic Volatil

CSA: Evaluarea Securității Chimice

CSR: Raportul Securității Chimice

DNEL: Nivel Derivat Fără Efect

EC50: Jumătate din Concentrația Efectivă Maximă

ECHA: Agenția Europeană pentru Produse Chimice

EINECS: Inventarul European al Substanțelor Chimice Existente pe piață

ES: Scenariul de Expunere

GefStoffVO: Ordonanță în legătură cu Substanțele Periculoase, Germania

GHS: Sistemul Mondial Armonizat de Clasificare și Etichetare a Produselor Chimice

IARC: Agenția Internațională pentru Cercetare în Domeniul Cancerului

IATA: Asociația Internațională de Transport Aerian

IC50: jumătate din concentrația inhibitorie maximă

IMDG: Coduri Maritime Internaționale pentru Bunurile Periculoase

LC50: Concentrația letală pentru un procent de 50% din populația test

LD50: Doza letală pentru un procent de 50% din populația test

LDLo: Doză Letală Scăzută

N.A.: Nu se aplică

N/A: Nu se aplică

N/D: Nedefinit/Nu este disponibil

N.D.: Nu este disponibil

NIOSH: Institutul Național pentru Securitate și Sănătate în Muncă

NOAEL: Nu există un Nivel al Efectelor Adverse Observat

OSHA: Administrația Securității și Sănătății în Muncă.

PBT: Persistente, Bioacumulative și Toxice
PGK: Instrucțiuni de ambalare
PNEC: Concentrația Fără Efect Prevăzută
PSG: Pasageri
RID: Regulamentul Referitor la Transportul Internațional de Bunuri Periculoase pe Calea Ferată
STEL: Limita de Expunere pe Termen Scurt
STOT: Toxicitatea pentru Organul Țintă Specific
TLV: Valoarea Limită a Pragului
TLV-TWA: Valoarea Limită a Pragului pentru Durata Ponderată Medie 8 ore pe zi (Standard ACGIH)
vPvB: Foarte Persistent, Foarte Bioacumulativ.
WGK: Clasa Germană a Periculozității Apei

Paragrafe modificate de la ultima revizuire:

- SECȚIUNEA 2: Identificarea pericolelor
- SECȚIUNEA 3: Compoziție/informații privind componenții
- SECȚIUNEA 6: Măsuri împotriva pierderilor accidentale
- SECȚIUNEA 8: Controale ale expunerii/protecția personală
- SECȚIUNEA 9: Proprietățile fizice și chimice
- SECȚIUNEA 11: Informații toxicologice
- SECȚIUNEA 12: Informații ecologice
- SECȚIUNEA 13: Considerații privind eliminarea
- SECȚIUNEA 14: Informații referitoare la transport
- SECȚIUNEA 15: Informații de reglementare
- SECȚIUNEA 16: Alte informații

Ethyl acetate

Substance identification

Chemical Name: Ethyl acetate

CAS number: 141-78-6

ETHYL ACETATE

ES 1: Cosmetics, personal care products (PC39); User for consumers (SU21).
 ES 2: Filling of drums and small packages (CS6); INDUSTRIAL USES (SU3).
 ES 3: Formulation or repackaging (F); INDUSTRIAL USES (SU3).
 ES 4: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4); Industrial uses (su3); Extraction agents (PC40).
 ES 5: PROFESSIONAL APPLICATION OF COATINGS AND INKS; INDUSTRIAL USES (SU3).
 ES 6: Use as laboratory reagent (PROC15); Industrial uses (su3); Industrial use.
 ES 7: Use in cleaning products (GEST4_I, GEST4_P, GEST4_C); INDUSTRIAL USES (SU3).
 ES 8: Use in lubricants (GEST6_I, GEST6_P, GEST6_C); INDUSTRIAL USES (SU3).
 ES 9: Professional application of coatings and inks (14); INDUSTRIAL USES (SU3). Covers use in coatings (paints, inks, adhesives, etc.) including exposures during use (receipt of material, storage, preparation and transfer of bulk and semi-bulk products, application by spray, roller or spreader, dipping, flow, fluidized bed on production lines and film formation), the cleaning and maintenance of the equipment and the associated laboratory activities [GES3_I].
 ES 10: Use as laboratory reagent (PROC15); Industrial uses (su3); Professional (G27).
 ES 11: Use in agrochemical products (GEST11_P, GEST11_C); INDUSTRIAL USES (SU3).
 ES 12: Use in detergent products (GEST4_I, GEST4_P, GEST4_C).
 ES 13: Use in lubricants (GEST6_I, GEST6_P, GEST6_C).
 ES 14: Adhesives, Sealants (PC1); Use in coatings (GEST3_I, GEST3_P, GEST3_C).

ES 5: PROFESSIONAL APPLICATION OF COATINGS AND INKS (17); INDUSTRIAL USES (SU3).

5.1. USE AT INDUSTRIAL SITES

Environment

SC 1: Use of non-reactive processing aid at industrial site (no inclusion in article) ERC4

Worker

SC 2: Generalized exposures (closed systems) PROC1
 SC 3: Generalized exposures (closed systems); Use in closed systems, with sample taking PROC2
 SC 4: Film formation - forced drying (50 -100°C). Stove (>100°C), Curing by UV/EB radiation PROC2
 SC 5: Mixing operations, Generalized exposures PROC3
 SC 6: Film formation, air drying PROC4
 SC 7: Preparation of material for application, Mixing operations (open systems) PROC5
 SC 8: Spraying (automatic/robotic) PROC7
 SC 9: Manual spraying PROC7
 SC 10: Material transfers, Non-Specialized site PROC8a
 SC 11: Material transfers, Specialized site PROC8b
 SC 12: Roller, diffusion, flow application PROC10
 SC 13: Immersion, dipping and pouring PROC13
 SC 14: Laboratory activities PROC15
 SC 15: Material transfers, Drum/batch transfers, Transfer from/pour from containers PROC9
 SC 16: Production or preparation of articles by tableting, compression, extrusion or pelletisation. PROC14

5.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

5.2.1 Environmental exposure control: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure

Daily amount per site: ≤ 1 t/day

Annual amount per site: ≤ 300 t/year

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Assumed domestic sewage treatment plant flow: ≥ 2E3 m³/day

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/g

5.2.2. Worker Exposure Control: Chemical production or refinement in closed processes without likelihood of exposure or in processes with equivalent containment conditions (PROC1)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.3. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.4. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.5. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.6. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.7. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.8. Worker Exposure Control: Industrial spraying (PROC7)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.9. Worker Exposure Control: Industrial spraying (PROC7)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.10. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.11. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.12. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.13. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.14. Worker Exposure Control: Use as laboratory reagents (PROC15)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.15. Worker Exposure Control: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.16. Worker Exposure Control: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

5.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Route release	Release rate	Method for estimating for release
water	20 kg/day	Estimated release factor
air	980 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Estimated exposure	RCR
Fresh water	0.119 mg/l (EUSES v2.1)	0.495
freshwater sediments	0.708 mg/kg dry weight (EUSES v2.1)	0.616
Sea water	0.012 mg/l (EUSES v2.1)	0.495
Marine sediment	0.071 mg/kg dry weight (EUSES v2.1)	0.617
Sewage treatment plant	1.184 mg/l (EUSES v2.1)	< 0.01
Farmland	0.081 mg/kg dry weight (EUSES v2.1)	0.547
Prey for predators (freshwater)	1.469 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.148 mg/kg dry weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.031 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.028 mg/kg dry weight (EUSES v2.1)	< 0.01

5.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	systemic	Short term	0.147 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Short term	0.147 mg/m ³ (ECETOC TRA worker v3)	< 0.01
dermal	systemic	Long-term	0.034 mg/kg bw/day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	< 0.01

5.3.3. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	1.37 mg/kg bw/day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.147

5.3.4. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	1.37 mg/kg bw/day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.147

5.3.5. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.69 mg/kg bw/day (ECETOC TRA worker v3)	0.011
combined routes	systemic	Long-term	/	0.261

5.3.6. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	36.71 mg/m ³ (ECETOC TRA worker v3)	0.05
inhalation	systemic	Short term	146.8 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	local	Long-term	36.71 mg/m ³ (ECETOC TRA worker v3)	0.05
inhalation	local	Short term	146.8 mg/m ³ (ECETOC TRA worker v3)	0.1
dermal	systemic	Long-term	6.86 mg/kg bw/day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.159

5.3.7. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.8. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	42.86 mg/kg bw/day (ECETOC TRA worker v3)	0.68
combined routes	systemic	Long-term	/	0.805

5.3.9. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	42.86 mg/kg bw/day (ECETOC TRA worker v3)	0.68
combined routes	systemic	Long-term	/	0.805

5.3.10. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.11. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	27.53 mg/m ³ (ECETOC TRA worker v3)	0.038
inhalation	systemic	Short term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.075
inhalation	local	Long-term	27.53 mg/m ³ (ECETOC TRA worker v3)	0.038
inhalation	local	Short term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.075
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.255

5.3.12. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	27.43 mg/kg bw/day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.56

5.3.13. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.14. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.34 mg/kg bw/day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.255

5.3.15. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	73.42 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	systemic	Short term	293.6 mg/m ³ (ECETOC TRA worker v3)	0.2
inhalation	local	Long-term	73.42 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	local	Short term	293.6 mg/m ³ (ECETOC TRA worker v3)	0.2
dermal	systemic	Long-term	6.86 mg/kg bw/day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.209

5.3.16. Worker exposure: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	3.43 mg/kg bw/day (ECETOC TRA worker v3)	0.054
combined routes	systemic	Long-term	/	0.179

5.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

ES 9: PROFESSIONAL APPLICATION OF COATINGS AND INKS (14); INDUSTRIAL USES (SU3). COVERS USE IN COATINGS (PAINTS, INKS, ADHESIVES, ETC.) INCLUDING EXPOSURES DURING USE (RECEIPT OF MATERIAL, STORAGE, PREPARATION AND TRANSFER OF BULK AND SEMI-BULK PRODUCTS, APPLICATION BY SPRAY, ROLLER OR SPREADER, DIPPING, FLOW, FLUIDIZED BED ON PRODUCTION LINES AND FILM FORMATION), THE CLEANING AND MAINTENANCE OF THE EQUIPMENT AND THE ASSOCIATED LABORATORY ACTIVITIES [GES3_I].

9.1. WIDE DISPERSIVE USE BY PROFESSIONAL WORKERS

Environment

SC 1: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) ERC8d

Worker

SC 3: Generalized exposures (closed systems) PROC1
SC 4: Filling of equipment from drums and containers PROC2
SC 5: Generalized exposures (closed systems), Use in closed systems PROC2
SC 6: Preparation of material for application, Generalized exposures PROC3
SC 7: Film formation - air drying, Indoor use PROC4
SC 8: Film formation - air drying, Outdoor use PROC4
SC 9: Preparation of material for application, Indoor use PROC5
SC 10: Preparation of material for application, Outdoor use PROC5
SC 11: Material transfers, Drum/batch transfers, Non-Specialized site PROC8a
SC 12: 12 Material Transfers, Drum/batch transfers, specialized site PROC8b
SC 13: Roller, diffusion, flow application, Indoor use PROC10
SC 14: Roller, diffusion, flow application, Outdoor use PROC10
SC 15: Manual spraying, Indoor use PROC11
SC 16: Manual spraying, Outdoor use PROC11
SC 17: Immersion, dipping and pouring, Indoor use PROC13
SC 18: Immersion, dipping and pouring, Outdoor use PROC13
SC 19: Laboratory activities PROC15
SC 20: Hand application - finger paints, crayons, stickers, Indoor use PROC19
SC 21: Hand application - finger paints, crayons, stickers, Outdoor use PROC19

9.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

9.2.1 Environmental exposure control: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) (ERC8d)

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

9.2.3. Worker Exposure Control: Chemical production or refinement in closed processes without likelihood of exposure or in processes with equivalent containment conditions (PROC1)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.4. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.5. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.6. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.7. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.8. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.9. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.10. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.11. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a) (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.12. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.13. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.14. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.15. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.16. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.17. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.18. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.19. Worker Exposure Control: Use as laboratory reagents (PROC15)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.20. Worker Exposure Control: Hand-mixing with direct contact and only PPE available (PROC19)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.21. Worker Exposure Control: Hand-mixing with direct contact and only PPE available (PROC19)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

9.3.1. Environmental release and exposure: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) (ERC8d)

Route release	Release rate	Method for estimating for release
water	0.014 kg/day	Estimated release factor
air	980 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Estimated exposure	RCR
Fresh water	0.000396 mg/l (EUSES v2.1)	< 0.01
freshwater sediments	0.00236 mg/kg dry weight (EUSES v2.1)	< 0.01
Sea water	0.0000597 mg/l (EUSES v2.1)	< 0.01
Marine sediment	0.000356 mg/kg dry weight (EUSES v2.1)	< 0.01
Sewage treatment plant	0.000805 mg/l (EUSES v2.1)	< 0.01
Farmland	0.000131 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (freshwater)	0.011 mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.00167 mg/kg wet weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.00158 mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.000114 mg/kg wet weight (EUSES v2.1)	< 0.01

9.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.367 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	systemic	Short term	1.468 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Long-term	0.367 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Short term	1.468 mg/m ³ (ECETOC TRA worker v3)	< 0.01
dermal	systemic	Long-term	0.034 mg/kg bw/day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	< 0.01

9.3.4. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	1.37 mg/kg bw/day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.272

9.3.5. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	1.37 mg/kg bw/day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.272

9.3.6. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	0.69 mg/kg bw/day (ECETOC TRA worker v3)	0.011
combined routes	systemic	Long-term	/	0.361

9.3.7. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	6.86 mg/kg bw/day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.284

9.3.8. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	6.86 mg/kg bw/day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.459

9.3.9. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.568

9.3.10. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.393

9.3.11. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.568

9.3.12. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg bw/day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

9.3.13. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	27.43 mg/kg bw/day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.785

9.3.14. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	27.43 mg/kg bw/day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.61

9.3.15. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.84
inhalation	local	Long-term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.84
dermal	systemic	Long-term	12.85 mg/kg bw/day (ECETOC TRA worker v3)	0.204
combined routes	systemic	Long-term	/	0.624

9.3.16. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	systemic	Short term	616.7 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	local	Long-term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	local	Short term	616.7 mg/m ³ (ECETOC TRA worker v3)	0.42
dermal	systemic	Long-term	12.85 mg/kg bw/day (ECETOC TRA worker v3)	0.204
combined routes	systemic	Long-term	/	0.414

9.3.17. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg bw/day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

9.3.18. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	systemic	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	local	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
dermal	systemic	Long-term	8.226 mg/kg bw/day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.183

9.3.19. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.34 mg/kg bw/day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.255

9.3.20. Worker exposure: Hand-mixing with direct contact and only PPE available (PROC19)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	systemic	Short term	1.32 g/m ³ (ECETOC TRA worker v3)	0.9
inhalation	local	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Short term	1.32 g/m ³ (ECETOC TRA worker v3)	0.9
dermal	systemic	Long-term	16.97 mg/kg bw/day (ECETOC TRA worker v3)	0.269
combined routes	systemic	Long-term	/	0.72

9.3.21. Worker exposure: Hand-mixing with direct contact and only PPE available (PROC19)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	5.657 mg/kg bw/day (ECETOC TRA worker v3)	0.09
combined routes	systemic	Long-term	/	0.44

9.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

ES 12: USE IN DETERGENT PRODUCTS (GEST4_I, GEST4_P, GEST4_C).

12.1. WIDE DISPERSIVE USE BY PROFESSIONAL WORKERS

Environment

SC 1: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) ERC8a

Worker

SC 2: Filling of equipment from drums and containers, specialised site PROC8b

SC 3: Automated process with (semi) closed systems; Use in closed systems PROC2

SC 4: Automated process with (semi) closed systems Drum/batch transfers, Use in closed systems PROC3

SC 5: Semi-automatic process (e.g: Semi-automatic application of floor care and maintenance products) PROC4

SC 6: Filling of equipment from drums and containers, Outdoor use PROC8a

SC 7: Immersion, dipping and pouring, Manual, Surfaces, Cleaning PROC13

SC 8: Cleaning with low-pressure washers, Roller application or brushing, No spraying PROC10

SC 9: Cleaning with high pressure washers, Spraying, Indoor use PROC11

SC 10: Cleaning with high pressure washers Spraying, Outdoor use PROC11

SC 11: Application of cleaning products in closed systems, Manual, Surfaces, Cleaning PROC10

SC 12: Ad hoc manual application via trigger sprays, partial dipping, etc., Roller application or brushing PROC10

SC 13: Application of cleaning products in closed systems, Outdoor use PROC4

SC 14: Cleaning of medical devices PROC4

12.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

12.2.1 Environmental exposure control: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) (ERC8a)

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

12.2.2. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.3. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.4. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.5. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.6. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.7. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.8. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.9. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.10. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 1%

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.11. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.12. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.13. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.14. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

12.3.1. Environmental release and exposure: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) (ERC8a)

Route release	Release rate	Method for estimating for release
water	0.014 kg/day	Environmental Release Category (ERC)
air	0.014 kg/day	Environmental Release Category (ERC)
Soil	0 kg/day	Environmental Release Category (ERC)

Protection target	Estimated exposure	RCR
Fresh water	0.000397 mg/l (EUSES v2.1)	< 0.01
freshwater sediments	0.00237 mg/kg dry weight (EUSES v2.1)	< 0.01
Sea water	0.000598 mg/l (EUSES v2.1)	< 0.01
Marine sediment	0.000357 mg/kg dry weight (EUSES v2.1)	< 0.01
Sewage treatment plant	0.000811 mg/l (EUSES v2.1)	< 0.01
Farmland	0.000131 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (freshwater)	0.011 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.00167 mg/kg dry weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.00158 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.000114 mg/kg dry weight (EUSES v2.1)	< 0.01

12.3.2. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg bw/day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

12.3.3. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
dermal	systemic	Long-term	0.822 mg/kg bw/day (ECETOC TRA worker v3)	0.013
combined routes	systemic	Long-term	/	0.163

12.3.4. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	0.414 mg/kg bw/day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.307

12.3.5. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	4.116 mg/kg bw/day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.29

12.3.6. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	77.09 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	systemic	Short term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	local	Long-term	77.09 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Short term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.21
dermal	systemic	Long-term	8.226 mg/kg bw/day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.236

12.3.7. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg bw/day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

12.3.8. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.9
inhalation	local	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.9
dermal	systemic	Long-term	16.45 mg/kg bw/day (ECETOC TRA worker v3)	0.261
combined routes	systemic	Long-term	/	0.711

12.3.9. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	21.42 mg/kg bw/day (ECETOC TRA worker v3)	0.34
combined routes	systemic	Long-term	/	0.64

12.3.10. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	2.143 mg/kg bw/day (ECETOC TRA worker v3)	0.034
combined routes	systemic	Long-term	/	0.384

12.3.11. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	5.486 mg/kg bw/day (ECETOC TRA worker v3)	0.087
combined routes	systemic	Long-term	/	0.437

12.3.12. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	16.45 mg/kg bw/day (ECETOC TRA worker v3)	0.261
combined routes	systemic	Long-term	/	0.561

12.3.13. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	systemic	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	local	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
dermal	systemic	Long-term	4.116 mg/kg bw/day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.118

12.3.14. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	systemic	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
dermal	systemic	Long-term	4.116 mg/kg bw/day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.215

12.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Substance identification

Chemical Name: bis-[4-(2,3-epoxipropoxy)phenyl]propane

CAS number: 1675-54-3

Date - Version: 29/12/2021 - 1.3

INDUSTRIAL USE - PROFESSIONAL USES: PUBLIC SECTOR (ADMINISTRATION, EDUCATION, ENTERTAINMENT, SERVICES, CRAFTS) (SU22).

1. TITLE SECTION

Exposure scenario name: Industrial use.

Structured short title: Professional uses: public sector (administration, education, entertainment, service, crafts) (SU22).

Substance: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC number: 216-823-5

Registration number: 01-2119456619-26

ENVIRONMENT

SC 1: Use of non-reactive processing aid at industrial site (no inclusion in article) ERC4

WORKER

SC 2: Use as laboratory reagents PROC15

SC 3: Treatment of articles by dipping and pouring PROC13

SC 4: Tableting, compression, extrusion, pelletising, granulation PROC14

SC 5: General greasing/lubrication in high energy conditions PROC18

SC 6 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8a

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. ENVIRONMENTAL EXPOSURE CONTROL: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Product features (article)

Physical form of the product: Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Daily amount per site: 0,6 ton/day

Annual amount per site: 20 ton/year

Conditions and measures related to sewage treatment plant

STP Type: Municipal wastewater treatment plant.

Learn more about STP: biological elimination.

STP sludge treatment: It may be landfilled when allowed by local regulations.

STP effluent: 2,000 m³/day

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/day

Outdoor / Indoor Indoor use.

2.2. WORKERS EXPOSURE CONTROL: Use as laboratory reagents (PROC15)

Product features (article)

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Temperature: < 40°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C

2.3. WORKERS EXPOSURE CONTROL: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 0%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C

2.4. WORKERS EXPOSURE CONTROL: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Product features (article)

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Temperature: < 40°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C

2.5. WORKERS EXPOSURE CONTROL: General greasing/lubrication in high energy conditions (PROC18)

Product features (article)

Covers concentrations up to 20%.

Physical form of the product: Liquid.

Temperature: ≤ 800°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Outside.

Industrial or professional environments: Professional use.

Temperature: ≤ 800°C

2.6. WORKERS EXPOSURE CONTROL: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC8a)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Outside.

Industrial or professional environments: Professional use.

Temperature: A process temperature of up to < 40°C is assumed.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Route release	Release rate	Method for estimating for release
water	1.2E-10kg/day	FEICA SPERC 5.1 a.v1
air	3E-4kg/day	FEICA SPERC 5.1 a.v1
Soil	0%	FEICA SPERC 5.1 a.v1

Protection target	Estimated Exposure (EUSES v2.1)	RCR
Fresh water	3.76E-4mg/l	0.063
Fresh water sediments	0.018mg/l	0.053
Sea water	2.95E-5mg/kg dry weight	0.049
Marine sediment	1.42E-3mg/kg dry weight	0.042
Sewage treatment plant	5.68E-11mg/l	< 0.01
Farmland	2.88E-6mg/kg dry weight	< 0.01
Prey for predators (freshwater)	mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	9.13E-4mg/kg wet weight	< 0.01
Main predator prey (marine water)	9.13E-4mg/kg wet weight	< 0.01
Prey for Predators (Terrestrial)	1.68E-4mg/kg wet weight	< 0.01
Man through the environment - inhalation	7.65E-9mg/m ³	< 0.01
Man through the environment - oral	3E-5mg/kgbw/day	< 0.01
Population exposed through the environment	-	< 0.01

3.2. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.993mg/m ³	0.201
inhalation	local	Long-term	0.993mg/m ³	-
inhalation	local	Short term	0.993mg/m ³	-
dermal	systemic	Long-term	0.172mg/kg bw/day	0.045
dermal	local	Short term	9.92E-3mg/cm ²	-
combined routes	-	-	-	0.247

3.3. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m ³	0.017
inhalation	local	Long-term	0.085mg/m ³	-
inhalation	local	Short term	0.085mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.06mg/cm ²	-
combined routes	-	-	-	0.566

3.4. Worker exposure: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.993mg/m ³	0.201
inhalation	local	Long-term	0.993mg/m ³	-
inhalation	local	Short term	0.993mg/m ³	-
dermal	systemic	Long-term	0.172mg/kg bw/day	0.229
dermal	local	Short term	0.0025mg/cm ²	-
combined routes	-	-	-	0.43

3.5. Worker exposure: General greasing/lubrication in high energy conditions (PROC18)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.596mg/m ³	0.121
inhalation	local	Long-term	0.596mg/m ³	-
inhalation	local	Short term	0.596mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.669

3.6. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.596mg/m ³	0.121
inhalation	local	Long-term	0.596mg/m ³	-
inhalation	local	Short term	0.596mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.669

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in Section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

PROFESSIONAL USE - PROFESSIONAL USES: PUBLIC SECTOR (ADMINISTRATION, EDUCATION, ENTERTAINMENT, SERVICES, CRAFTS) (SU22).

1. TITLE SECTION

Exposure scenario name: Professional.

Structured short title: Professional uses: public sector (administration, education, entertainment, service, crafts) (SU22).

Substance: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC number: 216-823-5

Registration number: 01-2119456619-26

ENVIRONMENT

SC 1: Use at an industrial site leading to inclusion in article ERC5

WORKER

SC 2: Industrial spraying PROC7

SC 3 Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8a

SC 4: Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at dedicated facilities. PROC8b

SC 5: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC9

SC 6: Application with rollers or brushes PROC10

SC 7: Non-industrial spraying PROC11

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. ENVIRONMENTAL EXPOSURE CONTROL: Use at an industrial site leading to inclusion in article (ERC5)

Product features (article)

Covers a percentage of substance in the product up to 100%.

Physical form of the product: Liquid

Amount used (or contained in articles), frequency and duration of use/exposure

Annual amount per site: 30,000 tons/year

Daily amount per site: 100 tons/day

Conditions and measures related to sewage treatment plant

STP Type: Municipal wastewater treatment plant.

Learn more about STP: biological elimination.

STP sludge treatment: It may be landfilled when allowed by local regulations.

STP effluent: 2,000 m³/day

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/day

2.2. WORKERS EXPOSURE CONTROL: Industrial spraying (PROC7)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

Wear suitable respirator.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Industrial or professional environments Professional use.

Temperature: Process temperature up to 70°C is assumed.

2.3. WORKERS EXPOSURE CONTROL: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities (PROC8a)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 0%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Industrial or professional environments Professional use.

Temperature: 70°C

2.4. WORKERS EXPOSURE CONTROL: Transfer of substance or mixture (charging/discharging) from/to vessels/large containers at dedicated facilities. (PROC8b)

Product features (article)

Covers the percentage of substance in the product up to 100%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: 70°C

2.5. WORKERS EXPOSURE CONTROL: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product features (article)

Covers concentrations up to 100%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 50°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 30%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 95%.

Inhalation: minimum yield of 0%.

Wear suitable respirator.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 50°C

2.6. WORKERS EXPOSURE CONTROL: Application with rollers or brushes (PROC10)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Vapour pressure: 0,00741 Pa

Temperature: < 70°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Assumes a good basic standard of occupational hygiene is implemented.

Provide a good standard of general ventilation (not less than 1 to 3 air changes per hour).

Local exhaust ventilation.

Dermal: minimum efficiency of 0%.

Inhalation: minimum yield of 90%.

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 0%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 70°C.

2.7. WORKERS EXPOSURE CONTROL: Non-industrial spraying (PROC11)

Product features (article)

Covers the percentage of substance in the product up to 25%.

Physical form of the product: Liquid.

Temperature: < 40°C

Amount used (or contained in articles), frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours.

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Use adequate eye protection.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

Wear suitable respirator.

Dermal: minimum efficiency of 99%.

Inhalation: minimum yield of 90%.

Other conditions affecting worker exposure

Outdoor / Indoor Inside.

Temperature: < 40°C.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Environmental release and exposure: Use at an industrial site leading to inclusion in article (ERC5)

Route release	Release rate	Method for estimating for release
water	0.06 kg/day	FEICA SPERC 8c.1 b.v1
air	0 kg/day	FEICA SPERC 8c.1 b.v1
Soil	0%	FEICA SPERC 8c.1 b.v1

Protection target	Estimated Exposure (EUSES v2.1)	RCR
Fresh water	3.22E-3mg/l	0,536
Fresh water sediments	0.155mg/l	0,454
Sea water	3.14E-4mg/l	0,523
Marine sediment	0.015mg/kg dry weight	0,442
Sewage treatment plant	0.028mg/l	< 0.01
Farmland	0.05mg/kg dry weight	0,779
Prey for predators (freshwater)	0.048mg/kg wet weight	< 0.01
Prey for predators (marine water)	4.53E-3mg/kg wet weight	< 0.01
Main predator prey (marine water)	1.64E-3mg/kg wet weight	< 0.01
Prey for Predators (Terrestrial)	0.056mg/kg wet weight	< 0.01
Man through the environment - inhalation	Concentration in air: 3.45E-11 mg/m³	< 0.01
Man through the environment - oral	1.47E-3mg/kg pc/giorno	< 0.01
Population exposed through the environment	-	< 0.01

3.2. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.34mg/m ³ (ART v1.5)	0.069
inhalation	local	Long-term	0.34mg/m ³ (ART v1.5)	-
inhalation	local	Short term	0.78mg/m ³ (ART v1.5)	-
dermal	systemic	Long-term	0.257mg/kgbw/day (ECETOC TRA worker v3)	0.343
dermal	local	Short term	0.012mg/cm ² (ECETOC TRA worker v3)	-
combined routes	-	-	-	0.412

3.3. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.851mg/m ³	0.173
inhalation	local	Long-term	0.851mg/m ³	-
inhalation	local	Short term	0.851mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.721

3.4. Worker exposure: Transfer of a substance or a mixture (fill/discharge) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m ³	0.017
inhalation	local	Long-term	0.085mg/m ³	-
inhalation	local	Short term	0.0851mg/m ³	-
dermal	systemic	Long-term	0.411mg/kgbw/day	0.548
dermal	local	Short term	0.03mg/cm ²	-
combined routes	-	-	-	0.566

3.5. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.099mg/m ³	0.02
inhalation	local	Long-term	0.099mg/m ³	-
inhalation	local	Short term	0.993mg/m ³	-
dermal	systemic	Long-term	0.343mg/kgbw/day	0.457
dermal	local	Short term	0.05mg/cm ²	-
combined routes	-	-	-	0.659

3.6. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure (ECETOC TRA worker v3)	RCR
inhalation	systemic	Long-term	0.085mg/m ³	0.017
inhalation	local	Long-term	0.085mg/m ³	-
inhalation	local	Short term	0.085mg/m ³	-
dermal	systemic	Long-term	0.165mg/kgbw/day	0.219
dermal	local	Short term	0.012mg/cm ²	-
combined routes	-	-	-	0.237

3.7. Worker exposure: Non-industrial spraying (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.34mg/m ³ (ART v1 .5)	0.069
inhalation	local	Long-term	0.34mg/m ³ (ART v1 .5)	-
inhalation	local	Short term	0.78mg/m ³ (ART v1 .5)	-
dermal	systemic	Long-term	0.643mg/kgbw/day (ECETOC TRA worker v3)	0.857
dermal	local	Short term	0.03mg/cm ² (ECETOC TRA worker v3)	-
combined routes	-	-	-	0.926

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Predicted exposures are not expected to exceed the applicable exposure limits (given in Section 8 of the SDS) when the operational conditions/risk management measures given in Section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Fișa cu date de securitate
ADYWOOD 2K COMP.B

Fișa cu date de securitate din data 10/09/2024 versiunea 2

SECȚIUNEA 1: Identificarea substanței/amestecului și a societății/întreprinderii
1.1. Identificator de produs

Identificarea preparatului:

Nume comercial: ADYWOOD 2K COMP.B

Cod comercial: 580.B

UFI: 1Y1H-H0UT-P00J-9JXM

1.2. Utilizări relevante identificate ale substanței sau ale amestecului și utilizări contraindicate

Utilizarea recomandată: Întăritor de poliamină

Utilizări de evitat: A se folosi numai de către utilizatori profesionali.

1.3. Detalii privind furnizorul fișei cu date de securitate

Compania: FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Responsabil: laboratorio.spresiano@fassabortolo.it

1.4. Număr de telefon care poate fi apelat în caz de urgență

+40213183606

SECȚIUNEA 2: Identificarea pericolelor

2.1. Clasificarea substanței sau a amestecului
Regulamentul (CE) nr. 1272/2008 (CLP)

Skin Irrit. 2 Provoacă iritarea pielii.
 Eye Dam. 1 Provoacă leziuni oculare grave.
 Skin Sens. 1 Poate provoca o reacție alergică a pielii.
 Aquatic Chronic 3 Nociv pentru mediul acvatic cu efecte pe termen lung.
 Efecte fizico-chimice dăunătoare sănătății omului și mediului înconjurător:
 Nici un alt risc

2.2. Elemente de etichetare
Regulamentul (CE) nr. 1272/2008 (CLP)
Pictograme de pericol și cuvânt de avertizare


Pericol

Fraze de pericol

H315 Provoacă iritarea pielii.
 H317 Poate provoca o reacție alergică a pielii.
 H318 Provoacă leziuni oculare grave.
 H412 Nociv pentru mediul acvatic cu efecte pe termen lung.

Fraze de precauție

P261 Evitați să inspirați vaporii.
 P273 Evitați dispersarea în mediu.
 P280 Purtați mănuși de protecție și protejați ochii/vederea.
 P302+P352 ÎN CAZ DE CONTACT CU PIELEA: spălați cu multă apă și săpun.
 P305+P351+P338 ÎN CAZ DE CONTACT CU OCHII: Clătiți cu atenție cu apă timp de mai multe minute. Scoateți lentilele de contact, dacă este cazul și dacă acest lucru se poate face cu ușurință. Continuați să clătiți.
 P310 Sunați imediat la un CENTRU DE INFORMARE TOXICOLOGICĂ/un medic.

Conține:

3-aminometil-3,5,5-trimetilciclohexilamină

Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină

Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină

Dispoziții speciale conform Anexei XVII (REACH) cu modificările și completările ulterioare:

Nici una

2.3. Alte pericole

Nu conține PBT, vPvB sau perturbatori endocrini prezenți în concentrații >= 0,1%.

Nici un alt risc

SECȚIUNEA 3: Compoziție/informații privind componenții

3.1. Substanțe

N.A.

3.2. Amestecuri

Identificarea preparatului: ADYWOOD 2K COMP.B

Componente periculoase în sensul Regulamentului CLP și clasificarea corespunzătoare:

Cantitate	Nume	Nr. de Ident.	Clasificare	Număr de înregistrare:
≥20 - <30 %	Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină	EC:701-046-0	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-2119972321-42-xxxx
≥10 - <20 %	Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
≥3 - <5 %	2,4,6-tris(dimetilaminometil)fenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Toxicitate Acută Estimată: ATE - Oral: 500mg/kg gc	01-2119560597-27-xxxx
≥1 - <3 %	3-aminometil-3,5,5-trimetilciclohexilamină	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Limite de concentrație specifice: C ≥ 0.001%: Skin Sens. 1A H317 Toxicitate Acută Estimată: ATE - Oral: 1030mg/kg gc	01-2119514687-32-xxxx

SECȚIUNEA 4: Măsuri de prim ajutor

4.1. Descrierea măsurilor de prim ajutor

În caz de contact cu pielea:

Îndepărtați imediat hainele contaminate și eliminați-l în mod sigur.

Zonele corpului care au venit, sau se presupune numai că au venit, în contact cu produsul trebuie spălate imediat și abundent cu apă curentă.

OBTINETI ASISTENTA MEDICALA IMEDIATA

În caz de contact cu ochii:

În caz de contact cu ochii, clătiți cu apă pentru un interval de timp corespunzător și țineți deschise pleoapele, după care consultați imediat un oftalmolog.

Protejați ochiul lezat.

În caz de ingerare:

Nu provocați vomitarea, adresați-vă unui medic arătând Fișa de Siguranță și eticheta produsului.

În caz de inhalare:

Conduceți accidentatul la aer liber și țineți-l la cald și în repaus.

4.2. Cele mai importante simptome și efecte, atât acute, cât și întârziate

Simptomele și efectele sunt cele preconizate în secțiunea 2 cu privire la pericole.

4.3. Indicații privind orice fel de asistență medicală imediată și tratamentele speciale necesare

În caz de accident sau stare proastă consultați imediat un medic (dacă este posibil arătați instrucțiunile de folosință sau fișa de siguranță).

SECȚIUNEA 5: Măsuri de combatere a incendiilor

5.1. Mijloace de stingere a incendiilor

Mijloace de stingere corespunzătoare:

CO₂, stingătoare cu pulbere, spumă, apă pulverizată.

Mijloace de stingere care nu trebuie să fie utilizate din motive de siguranță:

Jeturi de apă.

5.2. Pericole speciale cauzate de substanță sau de amestec

Combustia produce fum greu.

Nu inhalați gazele produse prin explozie și/sau prin combustie (monoxid de carbon, dioxid de carbon, oxizi de azot).

5.3. Recomandări destinate pompierilor

Folosiți dispozitive respiratorii corespunzătoare.

Strângeți separat apa contaminată folosită pentru stingerea incendiului. Nu o descărcați în rețeaua de canalizare.

Dacă este posibil din punct de vedere al siguranței, îndepărtați din zona de pericol imediat recipientele neafectate.

SECȚIUNEA 6: Măsuri împotriva pierderilor accidentale

6.1. Precauții personale, echipament de protecție și proceduri de urgență

Pentru personalul care nu este implicat în situații de urgență:

Îmbrăcați dispozitivele de protecție individuală.

Duceți persoanele în loc sigur.

Citiți măsurile de protecție prezentate la punctele 7 și 8.

Pentru personalul care intervine în situații de urgență:

Îmbrăcați dispozitivele de protecție individuală.

6.2. Precauții pentru mediul înconjurător

Împiedicați penetrarea în sol/subsol. Împiedicați vărsarea în apele de suprafață sau în rețeaua de canalizare.

În caz de scurgere de gaz sau penetrare în cursuri de apă, sol sau sistemul de canalizare, informați autoritățile răspunzătoare.

6.3. Metode și material pentru izolarea incendiilor și pentru curățenie

Material corespunzător pentru colectare: material absorbant inert (de exemplu, nisip, vermiculit)

Dupa ce produsul a fost recuperat, clătiți suprafața și materialele folosite cu apă

Rețineți apa de spălat contaminată și eliminați-o.

6.4. Trimiteri către alte secțiuni

Vezi și paragrafele 8 și 13

SECȚIUNEA 7: Manipulare și depozitare

7.1. Precauții pentru manipularea în condiții de securitate

Evitați contactul cu pielea și ochii, precum și inhalarea vaporilor și a ceții.

Nu folosiți recipiente goale înainte de a fi curățate.

Înainte operațiilor de transfer, asigurați-vă că în recipiente nu sunt materiale rezidue incompatibile.

Sfaturi privind igiena generală la locul de muncă:

Hainele contaminate trebuie înlocuite înainte de accesul la zona de prânz.

Nu mincați sau beți în timpul lucrului

Se face trimitere și la paragraful 8 pentru dispozitivele de protecție recomandate.

7.2. Condiții de depozitare în condiții de securitate, inclusiv eventuale incompatibilități

Păstrați recipientele bine închise într-un spațiu răcoros și bine ventilat, la distanță de surse de căldură.

Țineți departe de alimente, băuturi și hrană pentru animale.

Materiale incompatibile

Vezi pct. 10.5

Instrucțiuni privind spațiile de depozitare:

Spații ventilate adecvat

7.3. Utilizare (utilizări) finală (finale) specifică (specifice)

Recomandări

Vezi pct. 1.2

Soluții specifice pentru sectorul industrial

Nici o utilizare particulară

SECȚIUNEA 8: Controale ale expunerii/protecția personală

8.1. Parametri de control

Valori limită de expunere PNEC

Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină

Cale de expunere: Apă dulce; PNEC Limită: 2.63 µg/l

Cale de expunere: Apă sărată; PNEC Limită: 0.263 µg/l

Cale de expunere: Sedimente în apă dulce; PNEC Limită: 263.01 mg/kg

Cale de expunere: Sedimente în apă sărată; PNEC Limită: 26.301 mg/kg

Cale de expunere: Eliberări intermitente (apă dulce); PNEC Limită: 0.026 mg/l

Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 7.21 mg/l

Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină

CAS: 68082-29-1 Cale de expunere: Apă dulce; PNEC Limită: 0.004 mg/l

Cale de expunere: Apă sărată; PNEC Limită: 0 mg/l

Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 3.84 mg/l

Cale de expunere: Sedimente în apă dulce; PNEC Limită: 434.02 mg/kg

Cale de expunere: Sedimente în apă sărată; PNEC Limită: 43.4 mg/kg

Cale de expunere: Sol (agricol); PNEC Limită: 86.78 mg/kg

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2 Cale de expunere: Apă dulce; PNEC Limită: 0.046 mg/l

Cale de expunere: Apă sărată; PNEC Limită: 0.005 mg/l

Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 0.2 mg/l

Cale de expunere: Sedimente în apă dulce; PNEC Limită: 0.262 mg/kg

Cale de expunere: Sedimente în apă sărată; PNEC Limită: 0.026 mg/kg

Cale de expunere: Sol; PNEC Limită: 0.025 mg/kg

3-aminometil-3,5,5-trimetilciclohexilamină

CAS: 2855-13-2 Cale de expunere: Apă dulce; PNEC Limită: 0.06 mg/l

Cale de expunere: Apă sărată; PNEC Limită: 0.006 mg/l

Cale de expunere: Microorganisme în tratamente de epurare; PNEC Limită: 3.18 mg/l

Cale de expunere: Sedimente în apă dulce; PNEC Limită: 5.784 mg/kg

Cale de expunere: Sedimente în apă sărată; PNEC Limită: 0.578 mg/kg

Cale de expunere: Sol (agricol); PNEC Limită: 1.121 mg/kg

Nivel Derivat Fără Efect (DNEL)

Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină

Cale de expunere: Oral uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Consumator: 0.56

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 3.9 mg/m³; Consumator: 0.97 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 1.1 mg/kg; Consumator: 0.56 mg/m³

Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină

CAS: 68082-29-1 Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 0.952 mg/m³; Consumator: 0.169 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 0.272 mg/kg; Consumator: 97.2 µg/kg

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2 Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 0.53 mg/m³; Consumator: 0.13 mg/m³

Cale de expunere: Prin inhalare umană; Frecvență de expunere: Pe termen scurt, efecte sistemice
Lucrător profesionist: 2.1 mg/m³; Consumator: 0.13 mg/m³

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen lung, efecte sistemice
Lucrător profesionist: 0.15 mg/kg; Consumator: 0.075 mg/kg

Cale de expunere: Epidermic uman; Frecvență de expunere: Pe termen scurt, efecte sistemice
Lucrător profesionist: 0.6 mg/kg; Consumator: 0.075 mg/kg

8.2. Controale ale expunerii

Asigurați o ventilație adecvată. Atunci când este rezonabil posibil, aceasta se poate obține prin utilizarea de ventilație de schimb și a unei aspirații generale bune.

Protecția ochilor

Ochelari cu protecție laterală (EN 166).

Protecția pielii

Utilizați îmbrăcăminte corespunzătoare pentru protecția completă a pielii, în funcție de activitate și expunere (EN 14605/EN 13982), de exemplu salopetă de lucru, șorț, încălțăminte de siguranță, îmbrăcăminte corespunzătoare.

Protecția mainilor

Nu există niciun material sau combinație de materiale pentru mănuși care să poată garanta o rezistență nelimitată la orice produs chimic sau combinație de produse.

Pentru manipulare prelungită sau repetată, utilizați mănuși rezistente la produse chimice.

Tipul de mănuși adecvate (EN 374/EN 16523); FKM (fluor cauciuc): grosime ≥ 0.4 mm; timp de penetrare ≥ 480 min. NBR (cauciuc nitrilic): grosime ≥ 0.4 mm; timp de penetrare ≥ 480 min

Alegerea mănușilor potrivite nu depinde numai de material, ci și de alte caracteristici de calitate care variază de la un producător la altul, precum și de metodele și timpurile de utilizare a amestecului.

Protecție respiratorie

Dacă lucrătorii sunt expuși la concentrații mai mari decât limitele de expunere, trebuie să poarte aparate respiratorii certificate.

Filtru amestec (EN 14387): mască cu filtru A-P2.

Controale de expunere ambientală:

Vezi pct. 6.2

Măsurile de igienă și tehnice

Vezi alineatul 7.

SECȚIUNEA 9: Proprietățile fizice și chimice

9.1. Informații privind proprietățile fizice și chimice de bază

Aspect: lichid păstos

Culoare: maro închis

Miros: amină

Punctul de topire/punctul de înghețare: N.D.

Punctul de fierbere sau punctul inițial de fierbere și intervalul de fierbere: N.D.

Inflamabilitatea: N.A.

Limita inferioară și superioară de explozie: N.D.

Punctul de aprindere: $> 93^{\circ}\text{C}$

Temperatura de autoaprindere: N.D.

Temperatura de descompunere: N.D.

pH: N.A. (Nu se aplică datorită naturii produsului)

Viscozitatea cinematică: $> 20.5 \text{ mm}^2/\text{s}$ (40°C)

Densitatea și/sau densitatea relativă: 1,2 - 1,3 kg/l (Metoda internă)

Densitatea relativă a vaporilor: N.D.

Presiunea vaporilor: N.D.

Solubilitatea în apă: N.A.

Solubilitate în ulei: N.A.

Coeficientul de partiție n-octanol/apă (valoarea log): N.A.

Caracteristicile particulei:

Dimensiunea particulei: N.A.

9.2. Alte informații

Conductivitatea: N.D.

Proprietati explozive: N.A. (Evaluare internă)

Proprietati oxidante: N.A. (Evaluare internă)

Viteza de evaporare: N.A.

SECȚIUNEA 10: Stabilitate și reactivitate

10.1. Reactivitate

Stabilă în condiții normale

10.2. Stabilitate chimică

Stabilă în condiții normale

10.3. Posibilitatea de reacții periculoase

Se poate aprinde în contact cu agenți puternic oxidanți

Poate produce gaze inflamabile și/ sau toxice în contact cu metale elementare (alcalii și soluri alcaline), acizi minerali oxidanți,

substanțe organice halogenate, peroxizi și hidroperoxizi organici, agenți de oxidare puternici, agenți de reducere puternici.

10.4. Condiții de evitat

Evitați apropierea de surse de căldură.

10.5. Materiale incompatibile

Vezi pct. 10.3

10.6. Produși de descompunere periculoși

În cazul depozitării și manipulării adecvate, nu există produse de descompunere periculoase.

Vezi pct. 5.2

SECȚIUNEA 11: Informații toxicologice

11.1. Informații privind clasele de pericol definite în Regulamentul (CE) nr. 1272/2008

Informații toxicologice ale produsului:

a) toxicitate acută	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
b) corodarea/iritarea pielii	Produsul este clasificat: Skin Irrit. 2(H315)
c) lezarea gravă/iritarea ochilor	Produsul este clasificat: Eye Dam. 1(H318)
d) sensibilizarea căilor respiratorii sau a pielii	Produsul este clasificat: Skin Sens. 1(H317)
e) mutagenitatea celulelor germinative	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
f) cancerogenitatea	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
g) toxicitatea pentru reproducere	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
h) STOT (toxicitate asupra organelor țintă specifice) - expunere unică	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
i) STOT (toxicitate asupra organelor țintă specifice) - expunere repetată	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.
j) pericol prin aspirare	Neclasificat Pe baza datelor disponibile, criteriile de clasificare nu sunt îndeplinite.

Informații toxicologice referitoare la substanțele principale găsite în acest produs:

Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină

a) toxicitate acută	LD50 Oral Șobolan > 2000 mg/kg LD50 Piele Șobolan > 2000 mg/kg
---------------------	---

Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină

CAS: 68082-29-1	a) toxicitate acută	LD50 Oral Șobolan > 2000 LD50 Piele Șobolan > 2000
-----------------	---------------------	---

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2	a) toxicitate acută	ATE - Oral: 500 mg/kg gc LD50 Piele Șobolan > 1 mg/kg 6h
--------------	---------------------	---

3-aminometil-3,5,5-trimetilciclohexilamină

CAS: 2855-13-2	a) toxicitate acută	ATE - Oral: 1030 mg/kg gc
----------------	---------------------	---------------------------

11.2. Informații privind alte pericole

Proprietăți de perturbator endocrin:

Nu conține perturbatori endocrini prezenți în concentrații $\geq 0,1\%$

SECȚIUNEA 12: Informații ecologice

A se adopta bune practici de producție astfel încât produsul să nu fie eliberat în mediu

12.1. Toxicitate

Informații Ecotoxicologice:

Nociv pentru mediul acvatic cu efecte pe termen lung.

Lista proprietatilor Eco-toxicologice ale produsului

Produsul este clasificat: Aquatic Chronic 3(H412)

Lista componentelor cu proprietăți ecotoxicologice

Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină

- a) Toxicitate acvatică acută: LC50 Pește 7.07 mg/l 96h
- a) Toxicitate acvatică acută: EC50 Daphnia 5.18 mg/l 48h
- a) Toxicitate acvatică acută: EC50 Alge 2.63 mg/l 72h
- b) Toxicitatea acvatică cronică: NOEC Pește 5 mg/l
- b) Toxicitatea acvatică cronică: NOEC Alge 0.5 mg/l

Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină

- CAS: 68082-29-1
- a) Toxicitate acvatică acută: LC50 Pește 7.07 mg/l 96h
 - a) Toxicitate acvatică acută: EC50 Daphnia 5.18 mg/l 48h
 - a) Toxicitate acvatică acută: EC50 Alge 2.63 mg/l 72h
 - b) Toxicitatea acvatică cronică: NOEC Pește 5 mg/l
 - b) Toxicitatea acvatică cronică: NOEC Alge 0.5 mg/l

2,4,6-tris(dimetilaminometil)fenol

- CAS: 90-72-2
- a) Toxicitate acvatică acută: LC50 Pește 175 mg/l 96h
 - a) Toxicitate acvatică acută: LC50 Daphnia 718 mg/l 96h
 - a) Toxicitate acvatică acută: ErC50 Alge 84 mg/l 72h
 - a) Toxicitate acvatică acută: NOEC Alge 6.25 mg/l 72h

3-aminometil-3,5,5-trimetilciclohexilamină

- CAS: 2855-13-2
- a) Toxicitate acvatică acută: LC50 Pește 110 mg/l 96h
 - a) Toxicitate acvatică acută: EC50 Daphnia 23 mg/l 48h
 - a) Toxicitate acvatică acută: EC50 Alge > 50 mg/l 72h

12.2. Persistență și degradabilitate

Produs de reacție a acizilor grași, alchil C18 cu amine, fracțiunea polietilenpolitetraetilenopentamină

Nu este persistent și biodegradabil

Acizi grași, C18-nesaturați, dimeri, produse de reacție polimerică cu acizi grași cu ulei înalt și trietilenotetramină

CAS: 68082-29-1 Degradabil în mod lent

2,4,6-tris(dimetilaminometil)fenol

CAS: 90-72-2 Degradabil în mod lent

3-aminometil-3,5,5-trimetilciclohexilamină

CAS: 2855-13-2 Degradabil în mod lent

12.3. Potențial de bioacumulare

N.A.

12.4. Mobilitate în sol

N.A.

12.5. Rezultatele evaluărilor PBT și vPvB

În baza datelor disponibile, produsul nu conține substanțe PBT/vPvB în procentaj \geq de 0.1%.

12.6. Proprietăți de perturbator endocrin

Nu conține perturbatori endocrini prezenți în concentrații \geq 0,1%

12.7. Alte efecte adverse

N.A.

SECȚIUNEA 13: Considerații privind eliminarea

13.1. Metode de tratare a deșeurilor

A se recupera, dacă este posibil. A se trimite către punctele de depozitare sau de incinerare, în condiții controlate. A se respecta regulamentele locale în vigoare

Nu permiteți pătrunderea produsului în sistemul de canalizare sau în cursurile de apă.

Recipientele contaminate cu produs, în conformitate cu dispozițiile legale locale sau naționale.

SECȚIUNEA 14: Informații referitoare la transport

Nu sunt clasificate ca periculoase din punct de vedere al regulamentelor de transport

14.1. Numărul ONU sau numărul de identificare

N/A

14.2. Denumirea corectă ONU pentru expediție

ADR-Nume transport îmbarcare: N/A

IATA-Nume transport îmbarcare: N/A

IMDG-Nume transport îmbarcare: N/A

14.3. Clasa (clasele) de pericol pentru transport

ADR-clasa: N/A

IATA-Clasa: N/A

IMDG-Clasa: N/A

14.4. Grupul de ambalare

ADR-Grup Ambalare: N/A

IATA-Grup Ambalare: N/A

IMDG-Grup Ambalare: N/A

14.5. Pericole pentru mediul înconjurător

Poluant marin: Nu

Poluant ambiental: Nu

IMDG-EMS: N/A

14.6. Precauții speciale pentru utilizatori

Drumuri și Căi Ferate (ADR-RID):

scutiri ADR:

ADR-Etichetă: N/A

ADR - Număr de identificare a pericolului: N/A

ADR-Dispoziții Speciale: N/A

ADR-Cod de restricție în tunel:

Aer (IATA):

IATA-Aeronavă de pasagerit: N/A

IATA-Aeronavă de marfă: N/A

IATA-Etichetă: N/A

IATA-Riscul secundar: N/A

IATA-Erg: N/A

IATA-Dispoziții Speciale: N/A

Mare (IMDG):

IMDG-Depozitare și manipulare: N/A

IMDG-Segregare: N/A

IMDG-Riscul secundar: N/A

IMDG-Dispoziții Speciale: N/A

14.7. Transportul maritim în vrac în conformitate cu instrumentele OMI

N.A.

SECȚIUNEA 15: Informații de reglementare

15.1. Regulamente/legislație în domeniul securității, al sănătății și al mediului specifice (specifică) pentru substanța sau amestecul în cauză

Directiva 98/24/CE (Riscuri în legătură cu agenții chimici la locul de muncă)

Directiva 2000/39/CE (Valori limită a expunerii profesionale)

Directiva 2010/75/UE

Regulamentul (CE) nr. 1907/2006 (REACH)

Regulamentul (CE) nr. 1272/2008 (CLP)

Regulamentul (CE) nr. 790/2009 (ATP 1 CLP) și (EU) nr. 758/2013

Regulamentul (EU) nr. 2020/878

Regulamentul (EU) nr. 286/2011 (ATP 2 CLP)

Regulamentul (EU) nr. 618/2012 (ATP 3 CLP)

Regulamentul (EU) nr. 487/2013 (ATP 4 CLP)

Regulamentul (EU) nr. 944/2013 (ATP 5 CLP)

Regulamentul (EU) nr. 605/2014 (ATP 6 CLP)

Regulamentul (EU) nr. 2015/1221 (ATP 7 CLP)

Regulamentul (EU) nr. 2016/918 (ATP 8 CLP)

Regulamentul (EU) nr. 2016/1179 (ATP 9 CLP)
Regulamentul (EU) nr. 2017/776 (ATP 10 CLP)
Regulamentul (EU) nr. 2018/669 (ATP 11 CLP)
Regulamentul (EU) nr. 2018/1480 (ATP 13 CLP)
Regulamentul (EU) nr. 2019/521 (ATP 12 CLP)
Regulamentul (EU) nr. 2020/217 (ATP 14 CLP)
Regulamentul (EU) nr. 2020/1182 (ATP 15 CLP)
Regulamentul (EU) nr. 2021/643 (ATP 16 CLP)
Regulamentul (EU) nr. 2021/849 (ATP 17 CLP)
Regulamentul (EU) nr. 2022/692 (ATP 18 CLP)

Restricții referitoare la produsele sau substanțele conținute de acestea conform Anexei XVII Regulamentul (CE) 1907/2006 (REACH) cu modificările ulterioare:

Restricții referitoare la produs: 3
Restricții referitoare la substanțele conținute: 75

Dispoziții în legătură cu directiva EU 2012/18 (Seveso III):

Nici una

Regulamentul (UE) nr. 649/2012 (Regulamentul PIC)

Nu există substanțe menționate

Clasa Germană a Periculozității Apei

Clasa 3: foarte periculos.

Substanțe SVHC:

În baza datelor disponibile, produsul nu conține substanțe SVHC în procentaj \geq de 0.1%.

15.2. Evaluarea securității chimice

Nu a fost efectuată nici o Evaluare de Securitate Chimică pentru amestecul

SECȚIUNEA 16: Alte informații

Cod	Descriere
H302	Nociv în caz de înghițire.
H314	Provoacă arsuri grave ale pielii și lezarea ochilor.
H315	Provoacă iritarea pielii.
H317	Poate provoca o reacție alergică a pielii.
H318	Provoacă leziuni oculare grave.
H319	Provoacă o iritare gravă a ochilor.
H411	Toxic pentru mediul acvatic cu efecte pe termen lung.
H412	Nociv pentru mediul acvatic cu efecte pe termen lung.

Cod	Clasa de pericol și categoria de pericol	Descriere
3.1/4/Oral	Acute Tox. 4	Toxicitate acută (orală), Categoria 4
3.2/1B	Skin Corr. 1B	Corodarea pielii, Categoria 1B
3.2/2	Skin Irrit. 2	Iritarea pielii, Categoria 2
3.3/1	Eye Dam. 1	Lezarea gravă a ochilor, Categoria 1
3.3/2	Eye Irrit. 2	Iritarea ochilor, Categoria 2
3.4.2/1	Skin Sens. 1	Sensibilizarea pielii, Categoria 1
3.4.2/1A	Skin Sens. 1A	Sensibilizarea pielii, Categoria 1A
4.1/C2	Aquatic Chronic 2	Pericol cronic (pe termen lung) pentru mediul acvatic, Categoria 2
4.1/C3	Aquatic Chronic 3	Pericol cronic (pe termen lung) pentru mediul acvatic, Categoria 3

Clasificarea și procedura utilizate pentru realizarea clasificării pentru amestecuri în conformitate cu Regulamentul (CE) nr. 1272/2008 [CLP]:

Clasificare conform Regulamentului (CE) nr. 1272/2008	Procedura de clasificare
Skin Irrit. 2, H315	Metoda de calcul
Eye Dam. 1, H318	Metoda de calcul
Skin Sens. 1, H317	Metoda de calcul
Aquatic Chronic 3, H412	Metoda de calcul

Acest document a fost întocmit de un tehnician competent în domeniul SDS și care este pregătit în mod corespunzător.
Principalele surse bibliografice:

ECDIN - Rețeaua de date și informații de mediu privind produsele chimice - Centrul comun de cercetare, Comisia Comunităților Europene

SAX PROPRIETĂȚI PERICULOASE ALE MATERIALELOR INDUSTRIALE - Ediția a opta - Van Nostrand Reinold

Fișe tehnice de securitate ale furnizorilor de materii prime.

Aceste informații se bazează pe cunoștințele deținute la data menționată mai sus. Se referă numai la produsul menționat și nu constituie o garanție a calității pentru cazurile particulare

Este de datoria utilizatorului să se asigure că aceste informații sunt adecvate și corespund domeniului specific de utilizare

Această FTS anulează și înlocuiește pe cele emise anterior.

Legenda cu abrevierile și acronimele folosite în fișa cu date de securitate

ACGIH: Conferința Americană a Igieniştilor Industriali Guvernamentali

ADR: Acordul European referitor la Încărcătura Internațională de Bunuri Periculoase pe Drumuri

ATE: Toxicitate Acută Estimată

ATEmix: Estimarea toxicității acute (Amestecuri)

BEI: Index de Expunere Biologică

CAS: Chemical Abstracts Service (departament al Societății Americane de Chimie)

CAV: Centrul de Otrăvuri

CE: Comunitatea Europeană

CLP: Clasificare, Etichetare, Ambalare

CMR: Cancerigene, Mutagene și Toxice pentru reproducere

COV: Compus Organic Volatil

CSA: Evaluarea Securității Chimice

CSR: Raportul Securității Chimice

DNEL: Nivel Derivat Fără Efect

EC50: Jumătate din Concentrația Efectivă Maximă

ECHA: Agenția Europeană pentru Produse Chimice

EINECS: Inventarul European al Substanțelor Chimice Existente pe piață

ES: Scenariul de Expunere

GefStoffVO: Ordonanță în legătură cu Substanțele Periculoase, Germania

GHS: Sistemul Mondial Armonizat de Clasificare și Etichetare a Produselor Chimice

IARC: Agenția Internațională pentru Cercetare în Domeniul Cancerului

IATA: Asociația Internațională de Transport Aerian

IC50: jumătate din concentrația inhibitorie maximă

IMDG: Coduri Maritime Internaționale pentru Bunurile Periculoase

LC50: Concentrația letală pentru un procent de 50% din populația test

LD50: Doza letală pentru un procent de 50% din populația test

LDLo: Doză Letală Scăzută

N.A.: Nu se aplică

N/A: Nu se aplică

N/D: Nedefinit/Nu este disponibil

N.D.: Nu este disponibil

NIOSH: Institutul Național pentru Securitate și Sănătate în Muncă

NOAEL: Nu există un Nivel al Efectelor Adverse Observat

OSHA: Administrația Securității și Sănătății în Muncă.

PBT: Persistente, Bioacumulative și Toxice

PGK: Instrucțiuni de ambalare

PNEC: Concentrația Fără Efect Prevăzută

PSG: Pasageri

RID: Regulamentul Referitor la Transportul Internațional de Bunuri Periculoase pe Calea Ferată

STEL: Limita de Expunere pe Termen Scurt

STOT: Toxicitatea pentru Organul Țintă Specific

TLV: Valoarea Limită a Pragului

TLV-TWA: Valoarea Limită a Pragului pentru Durata Ponderată Medie 8 ore pe zi (Standard ACGIH)

vPvB: Foarte Persistent, Foarte Bioacumulativ.

WGK: Clasa Germană a Periculozității Apei

Paragrafe modificate de la ultima revizuire:

- SECȚIUNEA 2: Identificarea pericolelor
- SECȚIUNEA 6: Măsuri împotriva pierderilor accidentale
- SECȚIUNEA 8: Controale ale expunerii/protecția personală
- SECȚIUNEA 9: Proprietățile fizice și chimice
- SECȚIUNEA 11: Informații toxicologice
- SECȚIUNEA 12: Informații ecologice
- SECȚIUNEA 13: Considerații privind eliminarea

- SECȚIUNEA 14: Informații referitoare la transport
- SECȚIUNEA 16: Alte informații

2,4,6-tris(dimethylaminomethyl)phenol

Substance identification

Chemical Name: 2,4,6-tris(dimethylaminomethyl)phenol

CAS number: 90-72-2

EU index number: 603-069-00-0

EINECS number: 202-013-9

INDUSTRIAL APPLICATION OF COATINGS AND PAINTS - INDUSTRIAL USE

1. TITLE SECTION

Exposure scenario name: Industrial application of coatings and paints

Date - Version: 16/03/2020 - 1.0

Life cycle stage: Use at industrial sites

Main user group: Industrial uses

Sector(s) of use: Industrial uses (SU3)

Contributing scenario - Environment

CS1 Wet polymerization: ERC5

Contributing scenario - Worker

CS2 Roller, spray and stream application: PROC10

2. CONTRIBUTIVE SCENARIOS

2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC5)

Environmental release categories: Industrial use leading to inclusion into/onto an article (ERC5)

Product features (article)

Physical form of the product: Liquid

Amount used, frequency and duration of use

Amounts used:

Daily quantity per site ≤ 0.8 tons/day

Annual amount per site ≤ 20 tons/year

Release Type: Continuous release

Issue days: 220 days a year

Measures and technical-organizational conditions

Control measures to prevent releases: No substance input into waste water.

Conditions and measures relating to municipal sewage treatment plants

Type of sewage treatment plant (STP): Municipal STP

STP effluent (m³/day): 2000

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Collect and dispose of waste in accordance with local regulations. Refer to section 13.

Other operational conditions affecting environmental exposure

Flow rate of receiving surface water: 18000 m³/day

Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: For further data, see section 8 of the safety data sheet.

2.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Process categories: Roller and brush application (PROC10)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 0,075 Pa

Concentration of the substance in the product: Includes substance shares in the product up to 25%

Amount used, frequency and duration of use/exposure

Duration: Covers up to 8 hours of daily exposure.

Measures and technical-organizational conditions

Technical organizational measures:

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Inhalation - minimum 30% efficiency. Local aspiration system. Ensure operating personnel are trained to minimize exposure. Inhalation - minimum 90% efficiency.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:

During the specific training wear gloves resistant to chemicals (tested according to EN 374). Dermal - minimum 95% efficiency. Wear full face respirator conforming to EN136. Inhalation - minimum 99% efficiency. Wear waterproof clothing. Dermal - 97% minimum efficiency. For further data, see section 8 of the safety data sheet.

Other operational conditions affecting worker exposure

Temperature: A process temperature of up to 40°C is assumed.

Body parts exposed: Possible skin contact is believed to be limited to the hands.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC5)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.001 mg/l	EUSES	0.017
fresh water sediment	0.006 mg/kg	EUSES	< 1
sea water	0.000138 mg/l	EUSES	0.016
Marine sediment	0.000564 mg/kg	EUSES	< 1
ground	0.001 mg/kg	EUSES	< 1
sewage treatment plant	0 mg/l	EUSES	< 0.01
environmentally exposed people - Inhalation	2.5E-05 mg/l	EUSES	< 1

3.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.046 mg/m ³	chesar v 2.2	0.357
by inhalation, systemic, short-term	0.186 mg/m ³	chesar v 2.2	0.357
skin contact, systemic, long-term	0.025 mg/kg bw/day	chesar v 2.2	0.164
combined routes, systemic, long-term	N.d.	chesar v 2.2	0.521

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

INDUSTRIAL APPLICATION OF COATINGS AND PAINTS - PROFESSIONAL USE

1. TITLE SECTION

Exposure scenario name: Industrial application of coatings and paints

Date - Version: 16/03/2020 - 1.0

Life cycle stage: Generalized use by professional operators

Main user group: Professional uses

Sector(s) of use: Professional uses (SU22)

Contributing scenario - Environment

CS1 Wet polymerization: ERC8c

Contributing scenario - Worker

CS2 Roller, spray and stream application: PROC10

2. CONTRIBUTIVE SCENARIOS

2.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8c)

Environmental release categories: Widespread use resulting in inclusion in or on the surface of an article (indoor use) (ERC8c)

Product features (article)

Physical form of the product: Liquid

Amount used, frequency and duration of use

Amounts used: Quantity per use ≤ 0.000218 tons/year

Measures and technical-organizational conditions

Control measures to prevent releases: No entry of substance into waste water.

Conditions and measures relating to municipal sewage treatment plants

Type of sewage treatment plant (STP): Municipal STP Water - minimum efficiency of 0.059%.

STP effluent (m³/day): 2000

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Collect and dispose of waste in accordance with local regulations. Refer to section 13.

Other operational conditions affecting environmental exposure

Flow rate of receiving surface water: 18000 m³/day

Further information on good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: For further data, see section 8 of the safety data sheet.

2.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Process categories: Roller and brush application (PROC10)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 0,075 Pa

Concentration of the substance in the product: Includes substance shares in the product up to 25%

Amount used, frequency and duration of use/exposure

Duration: Includes use up to 4 hours.

Measures and technical-organizational conditions

Technical organizational measures:

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Inhalation - minimum 30% efficiency.

Local aspiration system. Ensure operating personnel are trained to minimize exposure. Inhalation - minimum 80% efficiency.

Provide supplementary ventilation and other openings. Inhalation - minimum efficiency of 44%.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:

During the specific training wear gloves resistant to chemicals (tested according to EN 374). Dermal - minimum 90% efficiency.

Wear full face respirator conforming to EN136. Inhalation - minimum 99% efficiency.

Wear waterproof clothing. Dermal - 97% minimum efficiency.

For further data, see section 8 of the safety data sheet.

Other operational conditions affecting worker exposure

Indoor use.

Temperature: A process temperature of up to 40°C is assumed.

Body parts exposed: Possible skin contact is believed to be limited to the hands.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. Contributing Scenario CS1 - Environment: Wet polymerization (ERC8c)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
fresh water	0.002 mg/l	EUSES	0.018
fresh water sediment	0.006 mg/kg	EUSES	< 1
sea water	0.000149 mg/l	EUSES	0.018
Marine sediment	0.000608 mg/kg	EUSES	< 1
ground	0.001 mg/kg	EUSES	< 1
sewage treatment plant	0.001 mg/l	EUSES	< 0.01
environmentally exposed people - Inhalation	1.03E-08 mg/l	EUSES	< 1

3.2. CS2 Contributing Scenario - Worker: Roller, spray and flow application (PROC10)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, systemic, long-term	0.078 mg/m ³	chesar v 2.2	0.599
by inhalation, systemic, short-term	0.52 mg/m ³	chesar v 2.2	1
skin contact, systemic, long-term	0.049 mg/kg bw/day	chesar v 2.2	0.329
combined routes, systemic, long-term	N.d.	chesar v 2.2	0.928

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Substance identification

Chemical Name: 3-aminomethyl-3,5,5-trimethylcyclohexylamine

CAS number: 2855-13-2

EU index number: 612-067-00-9

EINECS number: 220-666-8

ES1 Formulation or repackaging - INDUSTRIAL USES

1. TITLE SECTION

Exposure scenario name: Preparation and repackaging of substances and mixtures

Date - Version: 15/07/2020 - 1.0

Life cycle stage: Formulation or repackaging

Main user group: Industrial uses

Sector(s) of use: Industrial uses (SU3) - Large-scale production of basic chemicals (including petroleum products) (SU8) - Formulation [blending] of preparations and/or repackaging (SU10)

Contributing scenario - Environment

CS1 Wet formulation: ERC2

Contributing scenario - Worker

CS2 Use in closed systems: PROC3

CS3 Material Transfers: PROC8a

CS4 Material Transfers: PROC8b

CS5 Material Transfers: PROC9

CS6 Blend Operations: PROC5

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Environmental release categories: Formulation of mixtures (ERC2)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use

Amounts used: Annual amount per site 2500 t

Release Type: Continuous release

Issue days: 300 days/year

Further environmental conditions:

Wet formulation

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Measures and technical-organizational conditions

Control measures to prevent releases:

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Conditions and measures for the municipal sewage treatment plant

Type of sewage treatment plant (STP): Municipal STP

STP effluent (m³/day): 8640

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Do not spread industrial sludge on natural soils.

Other operational conditions affecting environmental exposure

Local seawater dilution factor: 100

Local fresh water dilution factor: 11

Flow rate of receiving surface water: 86400

Indoor use

2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Process categories: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment:

Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 95 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Process categories: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Process categories: Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 97%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Process categories: Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347.

Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Process categories: Mixing or Blending in Batch Processes (PROC5)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	4,258 mg/m ³	ECETOC TRA worker v2.0	0.212

3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	2,129 mg/m ³	ECETOC TRA worker v2.0	0.106
by inhalation, systemic, short-term	2,129 mg/m ³	ECETOC TRA worker v2.0	0.106

3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353

3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

ES2 Formulation or repackaging - PROFESSIONAL USES

1. TITLE SECTION

Exposure scenario name: Preparation and repackaging of substances and mixtures

Date - Version: 10/03/2020 - 1.0

Life cycle stage: Formulation or repackaging

Main user group: Professional uses

Sector(s) of use: Manufacture of bulk, large scale chemicals (including petroleum products) (SU8) - Formulation [mixing] of preparations and/or re-packaging (SU10) - Professional uses (SU22)

Contributing scenario - Environment

CS1 Wet formulation: ERC2

Contributing scenario - Worker

CS2 Use in closed systems: PROC3

CS3 Material Transfers: PROC8a

CS3 Material Transfers: PROC8b

CS3 Material Transfers: PROC9

CS6 Blend Operations: PROC5

2. CONDITIONS OF USE AFFECTING EXPOSURE

2.2. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Environmental release categories: Formulation of mixtures (ERC2)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use

Amounts used: Annual amount per site 2500 t

Release Type: Continuous release

Issue days: 300 days/year

Further environmental conditions:

Wet formulation

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Measures and technical-organizational conditions

Control measures to prevent releases:

Air - minimum efficiency of: 0.25 %

Ground - minimum efficiency of: 0.01 %

Water - minimum efficiency of: 0.5 %

Conditions and measures for the municipal sewage treatment plant

Type of sewage treatment plant (STP): Municipal STP

STP effluent (m³/day): 8640

Conditions and measures for waste treatment (including the product waste)

Waste treatment: Do not spread industrial sludge on natural soils.

Other operational conditions affecting environmental exposure

Local seawater dilution factor: 100

Local fresh water dilution factor: 11

Flow rate of receiving surface water: 86400

Indoor use

2.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Process categories: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 480 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 95 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Process categories: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure.

2.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Process categories: Transfer of a substance or a preparation (filling/emptying) at dedicated facilities (PROC8b)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Process categories: Transfer of a substance or preparation (filling/emptying) (dedicated filling line, including weighing) (PROC9)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 240 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

2.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Process categories: Mixing or Blending in Batch Processes (PROC5)

Product features (article)

Physical form of the product: Liquid

Vapor pressure: 1.57 Pa

Amount used, frequency and duration of use/exposure

Duration: 60 min

Frequency: 5 days/week

Measures and technical-organizational conditions

Technical organizational measures: For further data, see section 8 of the safety data sheet.

Conditions and measures related to personal protection, hygiene and health verification

Personal protective equipment: Wear suitable gloves, tested according to EN347. Dermal - minimum efficiency of: 98 %

Other operational conditions affecting worker exposure

Indoor use

Ventilation Rate: Provide a basic level of general ventilation (1 to 3 air changes per hour). 90%

Body parts exposed: Palm of a hand. Possible skin contact is believed to be limited to the hands.

Learn more about good practices. The requirements set out in the REACH Regulation Article 37(4) do not apply.

Further information on good practices: Wear waterproof clothing. Ensure regular inspection, cleaning and maintenance of machines and systems. Wear a suitable apron to avoid skin exposure. Wear suitable face protection.

3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

3.1. CS1 Environment Contributing Scenario: Wet Formulation (ERC2)

Protection target	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
sea water	1,025 kg/day	ECETOC TRA environment v2.0	0.81

3.2. CS2 Worker Contributing Scenario: Use in Closed Systems (PROC3)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	8,515 mg/m ³	ECETOC TRA worker v2.0	0.424

3.3. CS3 Worker Contributing Scenario: Material Transfers (PROC8a)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353
by inhalation, systemic, short-term	7,096 mg/m ³	ECETOC TRA worker v2.0	0.353

3.4. CS4 orker Contributing Scenario: Material Transfers (PROC8b)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

3.5. CS5 Worker Contributing Scenario: Material Transfers (PROC9)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706
by inhalation, systemic, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

3.6. CS6 Worker Contributing Scenario: Mixing Operations (PROC5)

Route of Exposure, Impact on Health, Exposure Indicator	Degree of exposure	Calculation method	Risk characterization ratio (RCR)
by inhalation, local, short-term	14,192 mg/m ³	ECETOC TRA worker v2.0	0.706

4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.